

RADIAL CATALOG 2016



**DEESTONE**

MOVE THE WORLD

## ABOUT **DEESTONE**

**DEESTONE LIMITED** was founded in 1977 by Mr. Suvit Vorgsaryavanich. The company's vision is to manufacture quality tyres for vehicles. Deestone's business philosophy "Integrity, Honesty, and Accountability" have resulted our company with worldwide reputation, qualifies with the global standards and trusted by more than 120 countries. With almost 40 years of experience Deestone has been producing quality tyres, while continuously developing every product to the highest standard. The use of new technology has allowed Deestone to create innovations that it meets specific application and use, which answers market demand. Deestone also concerns about environmental factors making our company environmental friendly. We ensure that all of our standard certification is up-to-date. All of our goals are to make our customers trust and proud when using our products.

All products of company serves various market demand which consist of high standard of production and certified with global standards. Deestone Group concentrates the after sales service to customers, with social responsibilities and warranty on the quality of company's products through all channel of communication with completely and clearly information. Product and brand image have been developing for highest customer satisfaction. We develop and produce quality tyres for all segments of vehicles to be a part of your journey.





# *CONTENT*

ABOUT US	02
RADIAL-PCR-UHP	05
RADIAL-LT - SUV	16

**DEESTONE**

MOVE THE WORLD



## *RADIAL PCR-UHP*

**DEESTONE**

## NAKARA R201

### FEATURES

1. Jointless spiral overlay
2. Two free tread block design.
3. Wide center rit
4. Round shoulder
5. Variable pitch sequence

### BENEFITS

1. Smooth and comfort driving performance.
2. Excellent breaking performance
3. Improved handling and stability
4. Good cornering
5. Quiet ride



SERIES	SIZES	LI	SS	SIDE WALL	RIM WIDTH		DIAMETER (MM)	WIDTH (MM)	TREAD DEPTH (MM)	MAX. LOAD		PRESSURE		UTQG		
					STANDARD (INCH)	APPROVAL (INCH)				(KG)	(LBS)	(PSI)	(kPa)	TREAD.	TRAC.	TEMP.
50	225/50R17	94	H	BSW	7.0	6.5 - 7.5	658	233	7.9	670	1480	44	300	500	A	A
	215/55R17	94	H	BSW	7.0	6.5 - 7.5	668	226	7.9	670	1480	44	300	500	A	A
55	205/55R16	91	H	BSW	5.5	6.0 - 7.0	632	214	7.9	615	1355	44	300	500	A	A
	185/60R14	82	H	BSW	5.5	5.0 - 6.0	578	189	8.1	475	1047	44	300	500	A	A
	195/60R15	88	V	BSW	5.0	5.5 - 6.5	615	201	7.8	560	1234	44	300	500	A	A
	205/60R15	91	H	BSW	5.0	5.5 - 6.5	627	209	7.9	615	1355	44	300	500	A	A
	215/60R16	95	H	BSW	5.5	6.0 - 7.0	664	221	7.9	690	1520	44	300	500	A	A
60	185/60R15	84	H	BSW	5.5	5.0 - 6.0	603	189	7.9	500	1100	44	300	500	A	A
	215/60R15	94	H	BSW	5.5	6.0 - 7.0	639	221	7.9	670	1480	44	300	500	A	A
	225/60R15	96	H	BSW	5.5	6.0 - 7.0	651	228	7.9	710	1565	44	300	500	A	A
	205/60R16	92	H	BSW	5.0	5.5 - 6.5	652	209	7.9	630	1390	44	300	500	A	A
	225/60R16	98	H	BSW	5.5	6.0 - 7.0	676	228	7.9	750	1655	44	300	500	A	A
	235/60R16	100	H	BSW	7.0	6.5 - 7.5	688	240	7.9	800	1765	44	300	500	A	A
	195/60R14	86	T	BSW	5.0	5.5 - 6.5	590	201	7.9	530	1160	44	300	500	A	A
65	165/65R13	77	T	BSW	5.0	4.5 - 5.5	544	170	7.6	412	908	44	300	500	A	A
	175/65R14	82	H	BSW	5.0	4.5 - 5.5	584	177	7.8	475	1047	44	300	500	A	A
	185/65R14	86	H	BSW	5.5	5.0 - 6.0	596	189	7.8	530	1168	44	300	500	A	A

## NAKARA R201

SERIES	SIZES	LI	SS	SIDE WALL	RIM WIDTH		DIAMETER (MM)	WIDTH (MM)	TREAD DEPTH (MM)	MAX. LOAD		PRESSURE		UTQG		
					STANDARD [INCH]	APPROVAL [INCH]				(KG)	(LBS)	(PSI)	(kPa)	TREAD.	TRAC.	TEMP.
65	185/65R15	88	H	BSW	5.5	5.0 - 6.0	621	189	7.8	560	1234	44	300	500	A	A
	215/65R15	96	H	BSW	6.5	5.0 - 7.0	661	221	7.9	710	1565	44	300	500	A	A
	195/65R15	91	H	BSW	6.0	5.5 - 6.5	635	201	7.9	615	1355	44	300	500	A	A
	205/65R15	94	H	BSW	6.0	5.5 - 6.5	647	209	7.9	670	1480	44	300	500	A	A
	215/65R16 XL	102	H	BSW	6.5	5.0 - 7.0	685	221	7.9	850	1875	50	340	500	A	A
	205/65R16	95	H	BSW	6.0	5.5 - 6.5	672	209	7.9	690	1520	44	300	500	A	A
	235/65R16	103	T	BSW	7.0	5.5 - 7.5	712	240	7.9	875	1930	44	300	500	A	A
	215/65R17	99	T	BSW	6.5	5.0 - 7.0	712	221	7.9	775	1710	44	300	500	A	A
70	165/70R13	79	T	BSW	5.0	4.5 - 5.5	562	170	7.6	437	963	44	300	500	A	A
	175/70R13	82	T	BSW	5.0	4.5 - 5.5	575	177	8.1	475	1047	44	300	500	A	A
	175/70R14	84	H	BSW	5.0	4.5 - 5.5	602	177	7.8	500	1102	44	300	500	A	A
	185/70R13	86	H	BSW	5.5	5.0 - 6.0	590	189	7.8	530	1168	44	300	500	A	A
	185/70R14	88	H	BSW	5.5	5.0 - 6.0	615	189	7.8	560	1234	44	300	500	A	A
	195/70R14	91	H	BSW	6.0	5.5 - 6.5	630	201	8.1	615	1356	44	300	500	A	A
	205/70R14 XL	98	H	BSW	6.0	5.5 - 6.5	644	209	8.1	750	1655	50	340	500	A	A
215/70R15	98	H	BSW	6.5	5.0 - 7.0	683	221	8.1	750	1655	44	300	500	A	A	

## NAKARA R202

SERIES	SIZES	LI	SS	SIDE WALL	RIM WIDTH		DIAMETER (MM)	WIDTH (MM)	TREAD DEPTH (MM)	MAX. LOAD		PRESSURE		UTQG		
					STANDARD [INCH]	APPROVAL [INCH]				(KG)	(LBS)	(PSI)	(kPa)	TREAD.	TRAC.	TEMP.
70	155/70R13	75	T	BSW	4.5	4.0 - 5.0	548	157	7.2	387	853	44	300	300	A	B
	155/70R12	73	T	BSW	4.5	4.0 - 5.0	523	157	6.9	365	805	44	300	240	A	A
80	155/80R13	79	T	BSW	4.5	4.0 - 5.0	578	157	6.9	437	963	44	300	240	A	A
	165R13	82	S	BSW	4.5	4.0 - 5.0	594	165	7.6	475	1047	44	300	300	A	B



# DEESTONE

MOVE THE WORLD



### NAKARA R301

SERIES	SIZES	LI	SS	SIDE WALL	RIM WIDTH		DIAMETER (MM)	WIDTH (MM)	TREAD DEPTH (MM)	MAX. LOAD		PRESSURE		UTQG		
					STANDARD (INCH)	APPROVAL (INCH)				(KG)	(LBS)	(PSI)	(kPa)	TREAD.	TRAC.	TEMP.
50	195/50R15	82	V	BSW	6.0	5.5 - 6.5	577	201	7.6	475	1047	44	300	500	A	A
	225/55R16	95	V	BSW	7.0	6.5 - 7.5	654	233	7.8	690	1521	44	300	500	A	A
	215/55R16 XL	97	V	BSW	7.0	6.5 - 7.5	642	226	7.8	730	1609	50	340	500	A	A
55	205/55R16	91	V	BSW	6.5	6.0 - 7.0	632	214	7.8	615	1356	44	300	500	A	A
	195/55R15	85	V	BSW	6.0	5.5 - 6.5	595	201	7.8	515	1135	44	300	500	A	A
60	185/55R15	82	V	BSW	6.0	5.5 - 6.5	585	194	7.8	475	1047	44	300	500	A	A
	215/60R16	95	V	BSW	6.5	6.0 - 7.0	664	221	8.1	690	1521	44	300	500	A	A
65	205/60R15	91	V	BSW	6.0	6.0 - 7.0	627	209	7.8	615	1356	44	300	500	A	A
	205/65R15	94	H	BSW	6.0	5.5 - 6.5	647	209	7.8	670	1477	44	300	500	A	A
	195/65R15	91	H	BSW	6.0	5.5 - 6.5	635	201	7.8	615	1355	44	300	500	A	A



### CARRERAS R701

SERIES	SIZES	LI	SS	SIDE WALL	RIM WIDTH		DIAMETER (MM)	WIDTH (MM)	TREAD DEPTH	MAX. LOAD		PRESSURE		UTQG		
					STANDARD (INCH)	APPROVAL (INCH)				(KG)	(LBS)	(PSI)	(kPa)	TREAD.	TRAC.	TEMP.
40	235/40ZR18 XL	95	W	BSW	8.5	8.0 - 9.0	645	241	7.7	690	1521	50	340	500	A	A
	225/40ZR18 XL	92	W	BSW	8.0	7.5 - 8.5	637	230	7.3	630	1389	50	340	500	A	A
	225/45ZR18 XL	95	W	BSW	7.5	7.0 - 8.0	659	225	7.3	690	1521	50	340	500	A	A
	225/45ZR17 XL	94	W	BSW	7.5	7.0 - 8.0	634	225	7.3	670	1477	50	340	500	A	A
45	215/45ZR17	87	W	BSW	7.0	6.5 - 7.5	626	213	7.5	545	1201	44	330	500	A	A
	205/45ZR17 XL	88	W	BSW	7.0	6.5 - 7.5	616	206	7.3	560	1234	50	340	500	A	A
	205/45ZR16 XL	87	W	BSW	7.0	6.5 - 7.5	590	206	7.7	545	1201	50	340	500	A	A
50	225/50ZR17	94	W	BSW	7.0	6.5 - 7.5	658	233	7.9	670	1477	44	330	500	A	A
	215/50ZR17	91	W	BSW	7.0	6.5 - 7.5	648	226	7.3	615	1355	44	330	500	A	A
	205/50ZR16	87	W	BSW	6.5	6.0 - 7.0	612	214	7.8	545	1201	44	330	500	A	A
	195/50ZR15	82	V	BSW	6.0	5.5 - 6.5	577	201	7.5	475	1047	44	330	500	A	A
55	215/55ZR17	94	W	BSW	7.0	6.5 - 7.5	668	226	7.3	670	1477	44	330	500	A	A



## CARRERAS R702

### FEATURES

1. Unidirectional and optimized tread design.
2. Round shoulder.
3. Large tread block profile.
4. Wide center rib.

### BENEFITS

1. Aggressive look and excellent sport riding.
2. Good cornering.
3. Enhanced responsive steering.
4. Improved handling and stability.



SERIES	SIZES	LI	SS	SIDE WALL	RIM WIDTH		DIAMETER (MM)	WIDTH (MM)	TREAD DEPTH (MM)	MAX. LOAD		PRESSURE		UTQG		
					STANDARD (INCH)	APPROVAL (INCH)				(KG)	(LBS)	(PSI)	(kPa)	TREAD.	TRAC.	TEMP.
30	225/30R20 XL	35	W	BSW	8.0	7.5 - 8.5	544	230	7.9	515	1140	50	340	500	A	A
35	245/35R20 XL	35	W	BSW	8.5	8.0 - 9.0	580	248	7.9	690	1520	50	340	500	A	A
40	245/43ZR16 XL	37	W	BSW	8.5	8.0 - 9.0	553	248	7.9	730	1610	50	340	500	A	A
	205/40R17 XL	34	W	DSW	7.5	7.0 - 8.0	596	212	7.9	500	1100	50	340	500	A	A
45	235/45ZR17 XL	37	W	BSW	8.0	7.5 - 8.5	544	236	7.9	730	1610	50	340	500	A	A
	225/45ZR16 XL	35	W	BSW	7.5	7.0 - 8.0	559	225	7.9	690	1520	50	340	500	A	A
	245/45ZR16 XL	30	W	BSW	8.0	7.5 - 8.5	577	243	7.9	800	1765	50	340	500	A	A
	245/45R17 XL	39	W	BSW	8.0	7.5 - 8.5	552	243	7.9	775	1710	50	340	500	A	A
	235/45R18 XL	38	W	BSW	8.0	7.5 - 8.5	569	236	7.9	750	1655	50	340	500	A	A
	205/45ZR16 XL	37	W	BSW	7.0	6.5 - 7.5	590	206	7.9	545	1200	50	340	500	A	A
50	205/45ZR17 XL	38	W	BSW	7.0	6.5 - 7.5	516	206	7.9	560	1234	50	340	500	A	A
	215/45ZR17	37	W	BSW	7.0	6.5 - 7.5	526	213	7.9	545	1200	44	300	500	A	A
	205/50R17	39	V	DSW	6.5	6.0 - 7.0	530	214	7.9	500	1200	44	340	500	A	A
	195/50R15	32	V	BSW	6.0	5.5 - 6.5	577	201	7.9	475	1050	44	340	500	A	A
	265/50R20 XL	111	V	BSW	8.5	8.0 - 9.0	774	277	8.6	1090	2405	50	340	500	A	A
55	205/50ZR16	37	W	BSW	6.5	6.0 - 7.0	512	214	7.9	545	1200	44	300	500	A	A
	225/55ZR17	37	W	BSW	7.0	6.5 - 7.5	580	233	7.9	730	1610	44	340	500	A	A
	215/55ZR17 XL	38	W	BSW	7.0	6.5 - 7.5	568	226	7.9	750	1655	50	340	500	A	A
	235/55R17	39	H	BSW	7.5	7.0 - 8.0	590	245	7.9	775	1710	44	340	500	A	A
	235/55R19	101	V	BSW	7.5	7.0 - 8.0	741	245	7.9	825	1820	44	340	500	A	A

# DEESTONE

MOVE THE WORLD



## CARRERAS RA801

SERIES	SIZES	LI	SS	SIDE WALL	RIM WIDTH		DIAMETER (MM)	WIDTH (MM)	TREAD DEPTH (MM)	MAX. LOAD		PRESSURE		UTQG		
					STANDARD (INCH)	APPROVAL (INCH)				(KG)	(LBS)	(PSI)	(kPa)	TREAD.	TRAC.	TEMP.
4E	245/40ZR18 XL	97	W	BSW	3.5	8.0 - 9.0	653	248	7.7	730	1610	50	340	260	AA	A
	225/45ZR17 XL	94	W	BSW	7.5	7.0 - 8.0	634	225	7.7	670	1480	50	340	260	AA	A
5C	215/50ZR17 XL	95	W	BSW	7	6.5 - 7.5	648	226	7.7	690	1520	50	340	260	AA	A
5E	205/55R16	91	V	BSW	5.5	6.0 - 7.0	632	214	7.7	615	1355	44	300	260	AA	A
	195/55R15	85	V	BSW	6	5.5 - 6.5	595	201	7.7	515	1140	44	300	260	AA	A



## W-TRAC R901

SERIES	SIZES	LI	SS	SIDE WALL	RIM WIDTH		DIAMETER (MM)	WIDTH (MM)	TREAD DEPTH (MM)	MAX. LOAD		PRESSURE		UTQG		
					STANDARD (INCH)	APPROVAL (INCH)				(KG)	(LBS)	(PSI)	(kPa)	TREAD.	TRAC.	TEMP.
45	195/45R16 XL	84	H	BSW	5.5	6.0 - 7.0	582	195	8.6	500	1100	50	340	-	-	-
	225/45R17 XL	94	H	BSW	7.5	7.0 - 8.0	634	225	8.6	670	1480	50	340	-	-	-
55	205/55R16	91	H	BSW	5.5	6.0 - 7.0	632	214	8.6	615	1355	44	300	-	-	-



## VINCENTE R203

SERIES	SIZES	LI	SS	SIDE WALL	RIM WIDTH		DIAMETER (MM)	WIDTH (MM)	TREAD DEPTH (MM)	MAX. LOAD		PRESSURE		UTQG		
					STANDARD (INCH)	APPROVAL (INCH)				(KG)	(LBS)	(PSI)	(kPa)	TREAD.	TRAC.	TEMP.
55	185/55R15	82	V	BSW	6.0	5.5 - 5.5	585	194	7.8	475	1050	44	300	540	A	A
	165/55R14	72	H	BSW	5.0	4.5 - 5.5	538	170	7.8	355	785	44	300	540	A	A
	175/60R13	77	H	BSW	5.0	4.5 - 5.5	540	177	7.8	412	910	44	300	540	A	A
	175/60R15	81	H	BSW	5.0	4.5 - 5.5	591	177	7.8	462	1020	44	300	540	A	A
60	205/60R14	88	H	BSW	6.0	5.5 - 6.5	602	209	7.8	560	1230	44	300	540	A	A
	185/60R15	84	H	BSW	5.5	5.0 - 6.0	603	189	7.8	500	1100	44	300	540	A	A
	165/60R14	82	H	BSW	5.5	5.0 - 6.0	578	189	7.8	475	1050	44	300	540	A	A
	165/60R13	73	H	BSW	5.0	4.5 - 5.5	528	170	7.8	365	800	44	300	540	A	A
	165/65R14	79	I	BSW	5.0	4.5 - 5.5	570	170	7.8	437	965	44	300	540	A	A
65	175/65R14	82	H	BSW	5.0	4.5 - 5.5	584	177	7.8	475	1050	44	300	540	A	A
	175/65R15	84	H	BSW	5.0	4.5 - 5.5	609	177	7.8	500	1100	44	300	540	A	A
	185/65R14	86	H	BSW	5.5	5.0 - 6.0	596	189	7.8	530	1160	44	300	540	A	A
	185/65R15	88	H	BSW	5.5	5.0 - 6.0	621	189	7.8	560	1230	44	300	540	A	A
	165/65R13	77	T	BSW	5.0	4.5 - 5.5	544	170	7.8	412	910	44	300	540	A	A
70	165/70R14	81	H	BSW	5.0	4.5 - 5.5	588	170	7.8	462	1020	44	300	540	A	A
	175/70R13	82	H	BSW	5.0	4.5 - 5.5	576	177	7.8	475	1050	44	300	540	A	A
	175/70R14	84	H	BSW	5.0	4.5 - 5.5	602	177	7.8	500	1100	44	300	540	A	A
	185/70R14	88	H	BSW	5.5	5.0 - 6.0	616	189	7.8	560	1230	44	300	540	A	A
	195/70R14	91	H	BSW	6.0	5.5 - 6.5	630	201	7.8	615	1355	44	300	540	A	A
185/70R13	86	H	BSW	5.5	5.0 - 6.0	590	189	7.8	530	1160	44	300	540	A	A	

# DEESTONE

MOVE THE WORLD



## VINCENTE R302

SERIES	SIZES	LI	SS	SIDE WALL	RIM WIDTH		DIAMETER (MM)	WIDTH (MM)	TREAD DEPTH (MM)	MAX. LOAD		PRESSURE		UTQG		
					STANDARD (INCH)	APPROVAL (INCH)				(KG)	(LBS)	(PSI)	(kPa)	TREAD.	TRAC.	TEMP.
30	265/30ZR19 XL	93	W	BSW	9.5	9.0 - 10.0	643	271	79	650	1435	50	340	420	A	A
35	235/35ZR19 XL	91	W	BSW	8.5	8.0 - 9.0	647	241	79	615	1355	50	340	420	A	A
40	225/40ZR18 XL	92	W	BSW	8.0	7.5 - 8.5	637	230	79	630	1390	50	340	420	A	A
	235/40ZR18 XL	95	W	BSW	8.5	8.0 - 9.0	645	241	79	690	1520	50	340	420	A	A
45	215/45ZR17	87	W	BSW	7.0	6.5 - 7.5	626	213	79	545	1200	44	300	420	A	A
	225/45ZR17 XL	94	W	BSW	7.5	7.0 - 8.0	634	225	79	670	1480	50	340	420	A	A
	225/45ZR18 XL	95	W	BSW	7.5	7.0 - 8.0	659	225	79	690	1520	50	340	420	A	A
50	195/50R15	82	V	BSW	6.0	5.5 - 6.5	577	201	79	475	1050	44	300	500	A	A
	205/50ZR17 XL	93	W	BSW	6.5	6.0 - 7.0	638	214	79	650	1435	50	340	420	A	A
	215/50ZR17	91	W	BSW	7.0	6.5 - 7.5	648	226	79	615	1355	44	300	420	A	A
	225/50ZR17	94	W	BSW	7.0	6.5 - 7.5	658	233	79	670	1480	44	300	420	A	A
	225/50R16	92	V	BSW	7.0	6.5 - 7.5	632	233	79	630	1390	44	300	500	A	A
	195/50R16 XL	88	V	BSW	6.0	5.5 - 6.5	602	201	79	560	1230	50	340	500	A	A
	185/55R15	82	V	BSW	6.0	5.5 - 6.5	585	194	79	475	1050	44	300	500	A	A
	185/55R16	83	V	BSW	6.0	5.5 - 6.5	610	194	79	487	1070	44	300	500	A	A
	195/55R15	86	V	BSW	6.0	5.5 - 6.5	595	201	79	515	1140	44	300	500	A	A
	195/55R16	87	V	BSW	6.0	5.5 - 6.5	620	201	79	545	1200	44	300	500	A	A
55	205/55R15	88	V	BSW	6.5	6.0 - 7.0	607	214	79	560	1230	44	300	500	A	A
	205/55R16	91	V	BSW	6.5	6.0 - 7.0	632	214	79	615	1355	44	300	500	A	A
	215/55R16 XL	97	V	BSW	7.0	6.5 - 7.5	642	226	79	730	1610	50	340	500	A	A
	215/55ZR17	94	W	BSW	7.0	6.5 - 7.5	668	226	79	670	1480	44	300	420	A	A
	225/55R16 XL	95	V	BSW	7.0	6.5 - 7.5	654	233	79	775	1710	50	340	500	A	A

## VINCENTE R302

SERIES	SIZES	LI	SS	SIDE WALL	RIM WIDTH		DIAMETER (MM)	WIDTH (MM)	TREAD DEPTH (MM)	MAX. LOAD		PRESSURE		UTQG		
					STANDARD (INCH)	APPROVAL (INCH)				(KG)	(LBS)	(PSI)	(kPa)	TREAD.	TRAC.	TEMP.
60	185/60R15	84	V	BSW	5.5	5.0 - 5.0	603	189	7.9	500	1100	44	300	500	A	A
	195/60R15	88	V	BSW	6.0	5.5 - 5.5	615	201	7.9	560	1230	44	300	500	A	A
	205/60R15	91	V	BSW	6.0	5.5 - 5.5	627	209	7.9	615	1355	44	300	500	A	A
	205/60R16	92	V	BSW	6.0	5.5 - 5.5	652	209	7.9	630	1390	44	300	500	A	A
	215/60R15	94	V	BSW	6.5	6.0 - 7.0	639	221	7.9	670	1480	44	300	500	A	A
	215/60R16	95	V	BSW	6.5	6.0 - 7.0	664	221	7.9	690	1520	44	300	500	A	A
	225/60R15	96	V	BSW	6.5	6.0 - 7.0	651	228	7.9	710	1565	44	300	500	A	A
	225/60R16	98	V	BSW	6.5	6.0 - 7.0	676	228	7.9	750	1655	44	300	500	A	A
	235/60R16	100	V	BSW	7.0	6.5 - 7.5	688	240	7.9	800	1765	44	300	500	A	A
	215/60R17	96	H	BSW	6.5	6.0 - 7.0	690	221	7.9	710	1565	44	300	500	A	A
	235/60R16	100	H	BSW	7.0	6.5 - 7.5	688	240	7.9	800	1765	44	300	500	A	A
	65	195/65R15	91	H	BSW	6.0	5.5 - 5.5	635	201	7.8	615	1355	44	300	500	A
205/65R15		94	H	BSW	6.0	5.5 - 5.5	647	209	7.9	670	1480	44	300	500	A	A
70	205/70R15	96	T	BSW	6.0	5.5 - 5.5	669	209	7.9	710	1565	44	300	500	A	A
80	155/80R13	79	H	BSW	4.5	4.0 - 5.0	578	157	7.9	437	965	44	300	500	A	A

# DEESTONE

MOVE THE WORLD



**VINGENTE R 203 VINGENTE R 302**



**MUD FLAWER R 405**

**MUD FLAWER R 408**

**DEESTONE**

MOVE THE WORLD



***RADIAL LT - SUV***



## PAYAK R401

### FEATURES

1. Double jointless spiral overlay
2. Four deep and wide grooves
3. Wide center rip
4. Round shoulder
5. Rim guard

### BENEFITS

1. Improved load capacity
2. Excellent hydroplaning resistance and wet traction
3. Improved handling and stability
4. Good cornering
5. Protection against wheel damage



SERIES	SIZES	LI	SS	PR	SIDE WALL	RIM WIDTH		DIAMETER (MM)	WIDTH (MM)	TREAD DEPTH (MM)	MAX. LOAD		PRESSURE		UTQG				
						STANDARD (INCH)	APPROVAL (INCH)				(KG)	(LBS)	(KG)	(LBS)	(PSI)	(kPa)	TREAD.	TRAC.	TEMP.
	195R14C	106/104	P	8	BSW	5.5	5.0-6.0	666	198	9	950	2095	900	1985	65	450	-	-	-

## PAYAK R402

### FEATURES

1. Free inner tread block design
2. Three deep and wide grooves
3. Large shoulder block design
4. Wide footprint and optimized contact patch

### BENEFITS

1. Excellent Breaking performance
2. Excellent hydroplaning resistance and wet traction
3. Enhanced responsive steering and good cornering
4. Reduced wear



SERIES	SIZES	LI	SS	PR	SIDE WALL	RIM WIDTH		DIAMETER (MM)	WIDTH (MM)	TREAD DEPTH (MM)	MAX. LOAD		PRESSURE		UTQG				
						STANDARD (INCH)	APPROVAL (INCH)				(KG)	(LBS)	(KG)	(LBS)	(PSI)	(kPa)	TREAD.	TRAC.	TEMP.
65	205/55R16C	107/105	R	8	BSW	6.0	5.5 - 6.5	672	209	9.1	975	2153	925	2340	69	475	-	-	-
	215/55R16C	109/107	R	8	BSW	6.5	6.0 - 7.0	666	221	9.4	1030	2273	975	2150	69	475	-	-	-
	235/55R16C	115/113	R	8	BSW	7.0	6.5 - 7.5	712	240	9.4	1215	2683	1150	2535	69	475	-	-	-
70	195/70R15C	104/102	R	8	BSW	6.0	5.5 - 6.5	655	201	9.5	900	1985	850	1875	65	450	-	-	-
	205/70R15C	106/104	Q	8	BSW	6.0	5.5 - 6.5	669	209	9.5	950	2094	900	1984	65	450	-	-	-
	215/70R15C	109/107	R	8	BSW	6.5	6.0 - 7.0	663	221	9.5	1030	2273	975	2150	65	450	-	-	-
	225/70R15C	112/110	R	8	BSW	6.5	6.0 - 7.0	697	228	9.4	1120	2473	1060	2335	65	450	-	-	-
75	205/75R16C	110/108	R	8	BSW	5.5	5.0 - 6.0	714	203	9.1	1060	2335	1000	2205	69	475	-	-	-
	215/75R16C	113/111	R	8	BSW	6.0	5.5 - 6.5	728	216	9.4	1150	2535	1090	2405	69	475	-	-	-
	225/75R16C	116/114	R	8	BSW	6.0	5.5 - 6.5	744	223	9.4	1250	2755	1180	2500	69	475	-	-	-

# DEESTONE

## PAYAK R403

### FEATURES

1. Aggressive tread design
2. Free small tread block design
3. Wide footprint and optimized contact patch

### BENEFITS

1. All-season performance
2. Excellent hydroplaning resistance and all weather traction
3. Enhanced responsive steering and



SERIES	SIZES	LI	SS	PR	SIDE WALL	RIM WIDTH		DIAMETER (MM)	WIDTH (MM)	TREAD DEPTH (MM)	MAX. LOAD		MAX. LOAD		PRESSURE		UTQG		
						STANDARD (INCH)	APPROVAL (INCH)				(KG)	(LBS)	(KG)	(LBS)	(PSI)	(kPa)	TREAD.	TRAC.	TEMP.
70	245/70R16	107	S		BSW	7	6.5 - 7.5	750	248	10	975	2149	-	-	44	300	-	-	-
	225/70R15C	109/107	S	6	BSW	6.5	6.0 - 7.0	697	228	9.3	1030	2270	975	2150	55	375	-	-	-

## PAYAK R404 A/T

### FEATURES

1. Four deep grooves
2. Large shoulder block design
3. Rim guard

### BENEFITS

1. Excellent hydroplaning resistance and wet traction
2. Enhanced responsive steering and good cornering
3. Protection against wheel damage



SERIES	SIZES	LI	SS	PR	SIDE WALL	RIM WIDTH		DIAMETER (MM)	WIDTH (MM)	TREAD DEPTH (MM)	MAX. LOAD		MAX. LOAD		PRESSURE		UTQG		
						STANDARD (INCH)	APPROVAL (INCH)				(KG)	(LBS)	(KG)	(LBS)	(PSI)	(kPa)	TREAD.	TRAC.	TEMP.
50	265/50R20*	107	T	-	BSW	8.5	8.0 - 9.0	774	277	9.6	975	2150	-	-	44	300	540	A	B
55	275/55R20 XL	117	T	-	BSW	8.5	8.0 - 9.0	810	284	9.6	1285	2835	-	-	50	340	540	A	B
	285/55R20*	115	T	-	BSW	9.0	8.5 - 9.5	822	297	9.6	1215	2680	-	-	44	300	540	A	B
60	265/60R18	110	T	-	BSW	8.0	7.5 - 8.5	775	272	9.6	1060	2335	-	-	44	300	540	A	B
	275/60R20	115	T	-	BSW	8.0	7.5 - 8.5	838	279	9.6	1215	2680	-	-	44	300	540	A	B
55	245/65R17	107	T	-	BSW	7.0	6.5 - 7.5	750	248	9.6	975	2150	-	-	44	300	540	A	B
	265/65R17	112	T	-	BSW	8.0	7.5 - 8.5	775	272	9.6	1120	2470	-	-	44	300	540	A	B
	275/65R18	116	T	-	BSW	8.0	7.5 - 8.5	815	279	9.6	1250	2755	-	-	44	300	540	A	B


## PAYAK R404 A/T

SERIES	SIZES	LI	SS	PR	SIDE WALL	RIM WIDTH		DIAMETER (MM)	WIDTH (MM)	TREAD DEPTH (MM)	MAX. LOAD		MAX. LOAD		PRESSURE		UTQG		
						STANDARD (INCH)	APPROVAL (INCH)				(KG)	(LBS)	(KG)	(LBS)	(PSI)	(kPa)	TREAD.	TRAC.	TEMP.
70	LT265/70R17	121/118	S	10	BSW/DWL	8.0	7.5 - 8.5	804	272	12.0	1450	319E	1320	2910	80	550	-	-	-
	LT285/70R17*	121/118	S	10	BSW	8.5	8.0 - 9.0	832	292	9.6	1450	319E	1320	2910	80	550	-	-	-
	235/70R16	106	T	-	BSW	7.0	6.5 - 7.5	736	240	9.6	950	209E	-	-	44	300	540	A	B
	245/70R16 XL	111	T	-	BSW	7.0	6.5 - 7.5	750	248	9.6	1090	240E	-	-	50	340	540	A	B
	245/70R17	110	T	-	BSW	7.0	6.5 - 7.5	776	248	9.6	1060	233E	-	-	44	300	540	A	B
	255/70R16	111	T	-	BSW	7.5	7.0 - 8.0	764	260	9.6	1090	240E	-	-	44	300	540	A	B
	265/70R16	112	T	-	BSW	8.0	7.5 - 8.5	778	272	9.6	1120	247C	-	-	44	300	540	A	B
	265/70R17	115	T	-	BSW	8.0	7.5 - 8.5	804	272	9.6	1215	268C	-	-	44	300	540	A	B
	265/70R1E	116	T	-	BSW	8.0	7.5 - 8.5	829	272	9.6	1250	275E	-	-	44	300	540	A	B
	285/70R17*	117	T	-	BSW	8.5	9.0 - 10.0	832	292	9.6	1285	283E	-	-	44	300	540	A	B
75	LT225/75R16	115/112	S	10	BSW/DWL	6.0	5.5 - 6.5	744	223	11	1215	268C	1120	2470	80	550	-	-	-
	LT235/75R15	104/101	S	6	BSW/DWL	6.5	6.0 - 7.0	733	235	11	900	198E	825	1820	50	350	-	-	-
	LT245/75R16	120/116	S	10	BSW/DWL	7.0	6.5 - 7.5	774	248	12.0	1400	308E	1250	2755	80	550	-	-	-
	LT245/75R17	121/118	S	10	BSW	7.0	6.5 - 7.5	800	248	12.1	1450	319E	1320	2910	80	550	-	-	-
	LT265/75R16	123/120	S	10	BSW/DWL	7.5	7.0 - 8.0	804	267	12.0	1550	341E	1400	3085	80	550	-	-	-
	LT285/75R16*	126/123	S	10	BSW	8.0	7.5 - 8.5	834	286	12.1	1700	375C	1550	3415	80	550	-	-	-
	235/75R1E	105	T	-	BSW	6.5	6.0 - 7.0	733	235	9.6	925	204C	-	-	44	300	540	A	B
	245/75R16*	111	T	-	BSW	7.0	6.5 - 7.5	774	248	9.6	1090	240E	-	-	44	300	540	A	B
265/75R16*	116	T	-	BSW	7.5	7.0 - 8.0	804	267	9.6	1250	275E	-	-	44	300	540	A	B	
E0	LT235/80R17	120/117	S	10	BSW	6.5	6.0 - 7.0	808	235	12.1	1400	308E	1285	2835	80	550	-	-	-
	LT215/85R16	115/112	S	10	BSW/DWL	6.0	5.5 - 6.5	772	216	11	1215	268C	1120	2470	80	550	-	-	-
E5	LT235/85R16	120/116	S	10	BSW/DWL	6.5	6.0 - 7.0	806	235	12	1400	308E	1250	2755	80	550	-	-	-
	30X9.50R15LT	104	S	6	BSW/DWL	7.5	7.0 - 8.0	750	240	12	900	198E	-	-	50	350	-	-	-
	31X10.50R15LT	109	S	6	BSW/DWL	8.5	8.0 - 9.0	775	268	12	1030	227C	-	-	50	350	-	-	-
	35X12.50R17LT*	121	S	10	BSW	10.0	9.5 - 10.5	877	318	12	1450	319E	-	-	65	450	-	-	-

# DEESTONE


MOVE THE WORLD

## PAYAK R406



SERIES	SIZES	LI	SS	PR	SIDE WALL	RIM WIDTH		DIAMETER (MM)	WIDTH (MM)	TREAD DEPTH (MM)	MAX. LOAD		MAX. LOAD		PRESSURE		UTQ3		
						STANDARD (INCH)	APPROVAL (INCH)				(KG)	(LBS)	(KG)	(LBS)	(PSI)	(kPa)	TREAD.	TRAC.	TEMP.
	5.50R13LT	97/95	P	12	BSW	4.0	3.5 - 4.5	622	151	8.9	730	1610	690	1520	91	625	-	-	-
	5.00R12LT	88/86	P	10	BSW	3.5	3.0 - 4.0	566	134	8.9	560	1230	530	1160	73	500	-	-	-

## PAYAK 007 R601



SERIES	SIZES	LI	SS	PR	SIDE WALL	RIM WIDTH		DIAMETER (MM)	WIDTH (MM)	TREAD DEPTH (MM)	MAX. LOAD		MAX. LOAD		PRESSURE		UTQ3		
						STANDARD (INCH)	APPROVAL (INCH)				(KG)	(LBS)	(KG)	(LBS)	(PSI)	(kPa)	TREAD.	TRAC.	TEMP.
5C	265/50R20	107	V	-	BSW	8.5	8.0 - 9.0	774	277	8.4	975	2150	-	-	44	300	560	A	A
	285/50R20	112	V	-	BSW	9.0	8.5 - 9.5	794	297	8.4	1120	2470	-	-	44	300	560	A	A
	225/55R17 XL	101	H	-	BSW	7.0	6.5 - 7.5	680	233	8.4	825	1820	-	-	50	340	560	A	A
5E	235/55R18 XL	104	V	-	BSW	7.5	7.0 - 8.0	715	245	8.4	900	1985	-	-	50	340	560	A	A
	255/55R18 XL	109	V	-	BSW	8.0	7.5 - 8.5	735	265	8.4	1030	2270	-	-	50	340	560	A	A
	275/55 R20 XL	117	V	-	BSW	8.5	8.5 - 9.5	810	284	8.4	1285	2835	-	-	50	340	560	A	A
	225/55R18*	98	V	-	BSW	7.0	6.5 - 7.5	705	233	8.4	750	1655	-	-	44	300	560	A	A
6C	265/60R18	110	H	-	BSW	8.0	7.5 - 8.5	775	272	8.4	1060	2335	-	-	44	300	560	A	A
	235/60R18 XL*	107	V	-	BSW	7.0	6.5 - 7.5	735	240	8.4	975	2150	-	-	50	340	560	A	A
	275/60R20*	115	H	-	BSW	8.0	7.5 - 8.5	835	279	8.4	1215	2680	-	-	44	340	560	A	A
	285/60R18*	116	V	-	BSW	8.5	8.0 - 9.0	795	292	8.4	1250	2755	-	-	44	340	560	A	A
	245/60R18*	105	V	-	BSW	7.0	6.5 - 7.5	751	248	8.4	925	2040	-	-	44	340	560	A	A
	225/60R18*	100	H	-	BSW	6.5	6.0 - 7.0	725	228	8.4	800	1765	-	-	44	340	560	A	A
6C	235/60R17*	102	H	-	BSW	7.0	6.5 - 7.5	714	240	8.4	850	1875	-	-	44	340	560	A	A
	225/60R17*	99	H	-	BSW	6.5	6.0 - 7.0	702	228	8.4	775	1710	-	-	44	340	560	A	A

## PYAK 007 R601

SERIES	SIZES	LI	SS	PR	SIDE WALL	RIM WIDTH		DIAMETER (MM)	WIDTH (MM)	TREAD DEPTH (MM)	MAX. LOAD		MAX. LOAD		PRESSURE		UTQG		
						STANDARD (INCH)	APPROVAL (INCH)				(KG)	(LBS)	(KG)	(LBS)	(PSI)	(kPa)	TREAD.	TRAC.	TEMP.
65	225/65R17	102	H	-	BSW	6.5	6.0 - 7.0	724	228	3.4	850	1875	-	-	44	300	563	A	A
	235/65R17 XL	108	H	-	BSW	7.0	6.5 - 7.5	738	240	3.4	1000	2205	-	-	50	340	563	A	A
	245/65R17 XL	111	H	-	BSW	7.0	6.5 - 7.5	750	248	3.4	1090	2405	-	-	50	340	563	A	A
	265/65R17	112	H	-	BSW/OWL	8.0	7.5 - 8.5	776	272	3.4	1120	2470	-	-	44	300	563	A	A
	275/65R18*	116	H	-	BSW	8.0	7.5 - 8.5	815	279	3.4	1250	2755	-	-	44	300	563	A	A
	215/65R16 XL*	102	H	-	BSW	6.5	6.0 - 7.0	686	221	3.4	850	1875	-	-	50	340	563	A	A
	265/65R18*	111	H	-	BSW	7.5	7.0 - 8.0	789	260	3.4	1090	2405	-	-	44	340	563	A	A
	285/65R17*	116	H	-	BSW	8.5	8.0 - 9.0	802	292	3.4	1250	2755	-	-	44	340	563	A	A
70	205/70R14 XL	98	H	-	BSW	6.0	5.5 - 6.5	644	209	3.2	750	1655	-	-	50	340	563	A	A
	205/70R15	96	H	-	BSW	6.0	5.5 - 6.5	669	209	3.2	710	1565	-	-	44	300	563	A	A
	215/70R15	90	H	-	DSW	6.5	6.0 - 7.0	680	221	3.2	750	1655	-	-	44	300	563	A	A
	215/70R16	100	H	-	BSW	6.5	6.0 - 7.0	708	221	3.4	800	1765	-	-	44	300	563	A	A
	225/70R15	100	H	-	BSW	6.5	6.0 - 7.0	697	228	3.4	800	1765	-	-	44	300	563	A	A
	225/70R16	103	H	-	BSW	6.5	6.0 - 7.0	722	228	3.4	875	1930	-	-	44	300	563	A	A
	235/70R16	106	H	-	BSW	7.0	6.5 - 7.5	736	240	3.4	950	2095	-	-	44	300	563	A	A
	235/70R17 XL	111	H	-	BSW	7.0	6.5 - 7.5	762	240	3.4	1090	2405	-	-	50	340	563	A	A
	245/70R16 XL	111	H	-	BSW	7.0	6.5 - 7.5	790	248	3.4	1090	2405	-	-	50	340	563	A	A
	245/70R17	110	H	-	BSW	7.0	6.5 - 7.5	776	248	3.4	1060	2335	-	-	44	300	563	A	A
	265/70R16	112	H	-	BSW/OWL	8.0	7.5 - 8.5	778	272	3.4	1120	2470	-	-	44	300	563	A	A
	265/70R17*	115	H	-	BSW	8.0	7.5 - 8.5	804	272	3.4	1215	2680	-	-	44	300	563	A	A
	265/70R18*	116	H	-	BSW	8.0	7.5 - 8.5	829	272	3.4	1250	2755	-	-	44	300	563	A	A
	255/70R18*	113	H	-	BSW	7.5	7.0 - 8.0	815	260	3.4	1150	2535	-	-	44	300	563	A	A
	255/70R16*	111	H	-	BSW	7.5	7.0 - 8.0	764	260	3.4	1090	2405	-	-	44	300	563	A	A
	235/70R15*	103	H	-	BSW	7.0	6.5 - 7.5	711	240	3.4	875	1930	-	-	44	300	563	A	A
235/75R15 XL*	109	T	-	BSW	6.5	6.0 - 7.0	733	235	3.4	1030	2270	-	-	50	340	563	A	A	
225/75R15*	102	T	-	BSW	6.0	5.5 - 6.5	719	223	3.4	850	1875	-	-	44	300	563	A	A	
265/75R16*	116	T	-	BSW	7.5	7.0 - 8.0	804	267	3.4	1250	2755	-	-	44	300	563	A	A	
245/75R16*	111	T	-	BSW	7.0	6.5 - 7.5	774	248	3.4	1090	2405	-	-	44	300	563	A	A	
225/75R16 XL*	108	T	-	BSW	6.0	5.5 - 6.5	744	223	3.4	1000	2205	-	-	50	340	563	A	A	
215/75R15*	100	T	-	BSW	6.0	5.5 - 6.5	703	216	3.4	800	1765	-	-	44	300	563	A	A	

# DEESTONE

MOVE THE WORLD

## PAYAK HT R602



SERIES	SIZES	LI	SS	PR	SIDE WALL	RIM WIDTH		DIAMETER (MM)	WIDTH (MM)	TREAD DEPTH (MM)	MAX. LOAD		MAX. LOAD		PRESSURE		UTQG		
						STANDARD (INCH)	APPROVAL (INCH)				(KG)	(LBS)	(KG)	(LBS)	(PSI)	(kPa)	TREAD.	TRAC.	TEMP.
6L	285/60R18	116	H	-	BSW	8.5	8.0 - 9.0	795	292	10	1250	2755	-	-	44	300	560	A	A
A5	285/65R17	116	H	-	BSW	8.5	8.0 - 9.0	802	292	10	1250	2755	-	-	44	300	560	A	A
	275/65R17	115	T	-	BSW	8	7.5 - 8.5	790	279	10	1215	2680	-	-	44	300	560	A	A
7C	275/70R16	114	T	-	BSW	8	7.5 - 8.5	792	279	10	1180	2600	-	-	44	300	560	A	A

## KACHA R101

### FEATURES

1. Double jointless spiral overlay
2. Four flat and wide ribs
3. Rim guard

### BENEFITS

1. Improved load capacity
2. Increased contact area delivers excellent handling
3. Protection against wheel damage



SERIES	SIZES	LI	SS	PR	SIDE WALL	RIM WIDTH		DIAMETER (MM)	WIDTH (MM)	TREAD DEPTH (MM)	MAX. LOAD		MAX. LOAD		PRESSURE		UTQG		
						STANDARD (INCH)	APPROVAL (INCH)				(KG)	(LBS)	(KG)	(LBS)	(PSI)	(kPa)	TREAD.	TRAC.	TEMP.
165R13C	94/92	R	8	8	BSW	4.5	4.0 - 5.0	596	167	8.2	670	1480	630	1390	65	450	-	-	-
185R14C	102/100	Q	8	8	BSW	5.5	5.0 - 6.0	650	188	8.6	850	1874	800	1764	65	450	-	-	-
195R14C*	106/104	P	8	8	BSW/WSW	5.5	5.0 - 6.0	666	198	9	950	2094	900	1984	65	450	-	-	-
195R15C	106/104	P	8	8	BSW	5.5	5.0 - 6.0	690	198	9	950	2094	900	1984	65	450	-	-	-
205R14C	109/107	P	8	8	BSW	6.0	5.5 - 6.5	684	208	9	1030	2505	975	2149	65	450	-	-	-
205R16C	110/108	R	8	8	BSW	6.0	5.5 - 6.5	736	208	9.5	1080	2335	1000	2205	65	450	-	-	-



## KACHA R102

SERIES	SIZES	LI	SS	PR	SIDE WALL	RIM WIDTH		DIAMETER (MM)	WIDTH (MM)	TREAD DEPTH (MM)	MAX. LOAD		MAX. LOAD		PRESSURE		UTQG		
						STANDARD (INCH)	APPROVAL (INCH)				(KG)	(LBS)	(KG)	(LBS)	(PSI)	(kPa)	TREAD	TRAC.	TEMP.
	195R14	100/104	R	8	BSW	5.5	5.0 - 6.0	665	198	7	950	2095	900	1985	65	450	-	-	-



## ST RADIAL R501

SERIES	SIZES	LOAD RANG	PR	SIDE WALL	RIM WIDTH		DIAMETER (MM)	WIDTH (MM)	TREAD DEPTH (MM)	MAX. LOAD		MAX. LOAD		PRESSURE		UTQG		
					STANDARD (INCH)	APPROVAL (INCH)				(KG)	(LBS)	(KG)	(LBS)	(PSI)	(kPa)	TREAD	TRAC.	TEMP.
75	ST205/75R14	C	6	BSW	5.5	5 - 5	664	203	7.2	800	1760	710	1570	50	350	-	-	-
	ST205/75R14	D	8	BSW	5.5	5 - 5	664	203	7.2	925	2040	825	1820	55	450	-	-	-
	ST205/75R15	C	6	BSW	5.5	5 - 5	689	203	7.2	825	1820	730	1610	50	350	-	-	-
	ST205/75R15	D	8	BSW	5.5	5 - 5	689	203	7.2	975	2150	850	1870	55	450	-	-	-
	ST215/75R14	C	6	BSW	6.0	5.5 - 5.5	678	216	7.2	850	1870	750	1650	50	350	-	-	-
	ST225/75R15	D	8	BSW	6.0	5.5 - 5.5	719	223	7.2	1150	2450	1000	2200	55	450	-	-	-
80	ST225/75R15	F	10	BSW	6.0	5.5 - 5.5	719	223	7.2	1285	2830	1120	2470	60	550	-	-	-
	ST235/80R16	E	10	BSW	6.5	6 - 7	782	235	7.8	1550	3420	1360	3000	30	550	-	-	-
	ST235/80R16	F	12	BSW	6.5	6 - 7	782	235	7.8	1650	3630	1490	3195	35	650	-	-	-
	ST175/80R13	C	6	BSW	5.0	4.5 - 5.5	610	177	7.0	615	1360	545	1200	50	350	-	-	-

# DEESTONE

MOVE THE WORLD

## R 200

### FEATURES

1. Double jointless spiral overlay
2. Perfect combination of tread blocks and grooves
3. Three deep and wide grooves

### BENEFITS

1. Improved load capacity
2. All-season performance
3. Excellent hydroplaning resistance on wet traction



SERIES	SIZES	LI	SS	PR	SIDE WALL	RIM WIDTH		DIAMETER (MM)	WIDTH (MM)	TREAD DEPTH (MM)	MAX. LOAD		PRESSURE		UTQG				
						STANDARD (INCH)	APPROVAL (INCH)				(KG)	(LBS)	(KG)	(LBS)	(PSI)	(kPa)	TREAD.	TRAC.	TEMP.
	155R12C	88/86	R	8	BSW	4.5	4.0 - 5.0	550	157	7.6	360	1235	530	1170	65	450	-	-	-

## MUD CLAWER R405 M/T

SERIES	SIZES	LI	SS	PR	SIDE WALL	RIM WIDTH		DIAMETER (MM)	WIDTH (MM)	TREAD DEPTH (MM)	MAX. LOAD		PRESSURE		UTQG				
						STANDARD (INCH)	APPROVAL (INCH)				(KG)	(LBS)	(KG)	(LBS)	(PSI)	(kPa)	TREAD.	TRAC.	TEMP.
7C	LT265/70R17	121/118	Q	10	BSW/OWL	8.0	7.5 - 8.5	810	272	14	1450	3195	1320	2910	60	550	-	-	-
	LT285/70R17	121/110	Q	10	BSW/OWL	8.5	8.0 - 9.0	830	292	15	1450	3195	1320	2910	60	550	-	-	-
	LT285/75R16	126/123	Q	10	BSW/OWL	8.0	7.5 - 8.5	840	286	14	1700	3750	1550	3415	60	550	-	-	-
	LT265/75R16	123/120	Q	10	BSW/OWL	7.5	7.0 - 8.0	810	267	14	1550	3415	1400	3085	60	550	-	-	-
7F	LT245/75R16	120/116	Q	10	BSW/OWL	7.0	6.5 - 7.5	780	248	14	1400	3085	1250	2755	60	550	-	-	-
	LT235/75R15	104/101	Q	6	BSW/OWL	6.5	6.0 - 7.0	739	235	15	900	1985	852	1820	50	350	-	-	-
	LT245/75R17	121/118	Q	10	BSW/OWL	7.0	6.5 - 7.5	806	248	15	1450	3195	1320	2910	60	550	-	-	-



## MUD CLAWER R405 M/T

SERIES	SIZES	LI	SS	PR	SIDE WALL	RIM WIDTH		DIAMETER (MM)	WIDTH (MM)	TREAD DEPTH (MM)	MAX. LOAD		MAX. LOAD		PRESSURE		UTQG		
						STANDARD (INCH)	APPROVAL (INCH)				(KG)	(LBS)	(KG)	(LBS)	(PSI)	(kPa)	TREAD.	TRAC.	TEMP.
85	LT235/85R16	120/116	Q	10	BSW/OWL	6.5	6.0 - 7.0	812	235	15	1400	3085	1250	2755	80	550	-	-	-
	33X12.50R15LT	'08	Q	6	BSW/OWL	10.0	9.5 - 10.5	832	318	16	1000	2205	-	-	35	250	-	-	-
	31X10.50R15LT	'09	Q	6	BSW/OWL	8.5	8.0 - 9.0	781	268	14	1030	2270	-	-	50	350	-	-	-
	30X9.50R15LT	'04	Q	6	BSW/OWL	7.5	7.0 - 8.0	756	240	15	900	1985	-	-	50	350	-	-	-
	35X12.50R18LT	'23	Q	10	BSW	10.0	9.5 - 10.5	883	318	16	1550	3415	-	-	65	450	-	-	-
	33X12.50R18LT	'18	Q	10	BSW	10.0	9.5 - 10.5	832	318	16	1320	2910	-	-	65	450	-	-	-
	35X12.50R20LT	'21	Q	10	BSW	10.0	9.5 - 10.5	883	318	16	1450	3195	-	-	65	450	-	-	-

## MUD CLAWER R408 M/T

SERIES	SIZES	LI	SS	PR	SIDE WALL	RIM WIDTH		DIAMETER (MM)	WIDTH (MM)	TREAD DEPTH (MM)	MAX. LOAD		MAX. LOAD		PRESSURE		UTQG		
						STANDARD (INCH)	APPROVAL (INCH)				(KG)	(LBS)	(KG)	(LBS)	(PSI)	(kPa)	TREAD.	TRAC.	TEMP.
70	JT 275/70R18	125/122	Q	10	BSW	8.0	7.5 - 8.5	849	279	15.2	1650	3640	1500	3305	80	550	-	-	-
	JT 295/70R17	121/118	Q	10	BSW	8.5	8.0 - 9.0	852	299	16.7	1450	3195	1320	2910	80	550	-	-	-
	JT 285/70R17	121/118	Q	10	BSW	8.5	8.0 - 9.0	838	292	15.2	1450	3195	1320	2910	80	550	-	-	-
	JT 265/70R17	121/118	Q	10	BSW	8.0	7.5 - 8.5	810	272	15.2	1450	3195	1320	2910	80	550	-	-	-
	LT245/75R17	121/118	Q	10	BSW	7.0	6.5 - 7.5	806	248	15	1450	3195	1320	2910	80	550	-	-	-
75	JT 285/75R16	126/123	Q	10	BSW	8.0	7.5 - 8.5	840	286	15.2	1700	3750	1550	3415	80	550	-	-	-
	JT 265/75R16	123/120	Q	10	BSW	7.5	7.0 - 8.0	810	267	15.2	1550	3415	1400	3085	80	550	-	-	-
	JT 245/75R16	120/116	Q	10	BSW	7.0	6.5 - 7.5	780	248	15.2	1400	3085	1250	2755	80	550	-	-	-
85	JT 235/75R15	104/101	Q	6	BSW	6.5	6.0 - 7.0	739	235	14.7	900	1985	825	1820	50	350	-	-	-
	LT235/85R16	120/116	Q	10	BSW	6.5	6.0 - 7.0	812	235	15.0	1400	3085	1250	2755	80	550	-	-	-



# DEESTONE

MOVE THE WORLD

## MUD CLAWER R408 M/T

SERIES	SIZES	LI	SS	PR	SIDE WALL	RIM WIDTH		DIAMETER (MM)	WIDTH (MM)	TREAD DEPTH (MM)	MAX. LOAD		MAX. LOAD		PRESSURE		UTQG		
						STANDARD (INCH)	APPROVAL (INCH)				(KG)	(LBS)	(KG)	(LBS)	(PSI)	(kPa)	TREAD.	TRAC.	TEMP.
	33X12.50R15L1	108	Q	6	BSW	10.0	9.5 - 10.5	832	318	16.7	1000	2205	-	-	35	250	-	-	-
	31X10.50R15LT	109	Q	6	BSW	8.5	8.0 - 9.0	781	268	14.7	1030	2270	-	-	50	350	-	-	-
	30X9.50R15L <sup>~</sup>	104	Q	6	BSW	7.5	7.0 - 8.0	756	240	14.7	900	1985	-	-	50	350	-	-	-
	35X12.50R17LT	121	Q	10	BSW	10.0	9.5 - 10.5	883	318	16.7	1450	3195	-	-	65	450	-	-	-
	35X12.50R18LT	123	Q	10	BSW	10.0	9.5 - 10.5	883	318	16.7	1550	3415	-	-	65	450	-	-	-
	33X12.50R18LT	118	Q	10	BSW	10.0	9.5 - 10.5	832	318	16.7	1320	2910	-	-	65	450	-	-	-
	35X12.50R20LT	121	Q	10	BSW	10.0	9.5 - 10.5	883	318	16.7	1450	3195	-	-	65	450	-	-	-
	33X12.50R20LT	114	Q	10	BSW	10.0	9.5 - 10.5	832	318	15.2	1180	2600	-	-	65	450	-	-	-
	35X12.50R18LT	123	Q	10	BSW	10.0	9.5 - 10.5	883	318	16.7	1550	3415	-	-	65	450	-	-	-
	33X12.50R18LT	118	Q	10	BSW	10.0	9.5 - 10.5	832	318	16.7	1320	2910	-	-	65	450	-	-	-
	35X12.50R17LT	121	Q	10	BSW	10.0	9.5 - 10.5	883	318	16.7	1450	3195	-	-	65	450	-	-	-
	33X12.50R15LT	108	Q	6	BSW	10.0	9.5 - 10.5	832	318	16.7	1000	2205	-	-	35	250	-	-	-
	31X10.50R15LT	109	Q	6	BSW	8.5	8.0 - 9.0	781	268	14.7	1030	2270	-	-	50	350	-	-	-
	30X9.50R15L <sup>~</sup>	104	Q	6	BSW	7.5	7.0 - 8.0	756	240	14.7	900	1985	-	-	50	350	-	-	-
	35X12.50R22LT*	117	Q	10	BSW	10.0	9.5 - 10.5	883	318	16.7	1285	2835	-	-	65	450	-	-	-
	37x12.50R20LT**	126	Q	10	BSW	10.0	9.5 - 10.5	934	318	16.7	1700	3750	-	-	65	450	-	-	-
	37x13.50R22LT**	123	Q	10	BSW	11.0	10.5 - 11.5	934	345	16.7	1550	3415	-	-	65	450	-	-	-



**DEESTONE**

MOVE THE WORLD



Product may not be available in some country. Please contact us for more information.

**SVIZZ-ONE CORPORATION COMPANY LIMITED**

4/1 B Moo 7, Banglane Koh-at Road, Bangpla  
Banglane, Nakompathom 73130 Thailand

Tel : (+66 34) 234 927-30, 023 4756-30 Fax : (+66 34) 926 467

Email : [global-business@deestone.com](mailto:global-business@deestone.com)

Website : [www.deestone.com](http://www.deestone.com)