

ON THE ROAD
CATALOG



DEESTONE

MOVE THE WORLD

ABOUT *DEESTONE*

DEESTONE was founded in 1977 by Mr. Suvit Vongsariyavanich. The company's vision is to manufacture quality tires for vehicles. Deestone's business philosophy "Integrity, Honesty, and Accountability" have resulted our company with worldwide reputation, qualifies with the global standards and trusted by more than 120 countries. With over 40 years of experience Deestone has been producing quality tires, while continuously developing every product to the highest standard. The use of new technology has allowed Deestone to create innovations that it meets specific application and use, which answers market demand. Deestone also concerns about environmental factors making our company environmental friendly. We ensure that all of our standard certification is up-to-date. All of our goals are to make our customers trust and proud when using our products.

All products of company serves various market demand which consist of high standard of production and certified with global standards. Deestone Group offers the after sales service to customers, with social responsibilities and warranty on the quality of company's products through all channel of communication with completely and clearly information. Product and brand image have been developing for highest customer satisfaction. We develop and produce quality tires for all segments of vehicles to be a part of your journey.



CONTENT

ABOUT US	2
TRUCK OR BUS	4
LIGHT TRUCK	8
ULTRA LIGHT TRUCK	11
MILITARY	14
TRAILER	16

TRUCK OR BUS



**D103****D104****D106****D107****D108****D109**

PATTERN NAME	SIZE	PLY RATING	LI/SS	TYPE	INFLATED DIMENSION		TREAD DEPTH mm	INFLATION PRESSURE SINGLE PSI/kPa	MAX. LOAD SINGLE kgs/lbs	INFLATION PRESSURE DUAL PSI/kPa	MAX. LOAD DUAL kgs/lbs	RIM WIDTH inch
					OD (mm)	SW (mm)						
D103	8 25-20	14	136/132L	TT	974	236	14.0	115/790	2240/4940	105/720	2000/4410	6.5
	9.00-20	14	141/137L	TT	1019	259	13.5	110/760	2575/5675	100/690	2300/5070	7.0
		16	144/140L	TT	1019	259	13.5	125/860	2800/6175	115/790	2500/5510	7.0
D104	10.00-20	14	144/139L	TT	1054	278	13.9	100/690	2800/6175	90/620	2430/5355	7.5
		16	146/142L	TT	1054	278	13.9	115/790	3000/6610	105/720	2650/5840	7.5
	11.00-20	16	150/145L	TT	1085	293	11.5	115/790	3350/7390	105/720	2900/6395	8.0
D106	10.00-20	16	146/142L	TT	1054	278	13.4	115/790	3000/6610	105/720	2650/5840	7.5
	12.00-20	16	152/148L	TT	1125	315	12.0	105/720	3550/7830	95/660	3150/6940	8.5
		18	154/150L	TT	1125	315	12.0	115/790	3750/8270	105/720	3350/7390	8.5
D107	9.00-20	14	141/137L	TT	1019	259	14.4	110/760	2575/5675	100/690	2300/5070	7.0
	10.00-20	16	146/142L	TT	1054	278	15.4	115/790	3000/6610	105/720	2650/5840	7.5
	11.00-20	16	150/145L	TT	1085	293	16.8	115/790	3350/7390	105/720	2900/6395	8.0
D108	9 00-20	14	141/137L	TT	1019	259	14.9	110/760	2575/5675	100/690	2300/5070	7.0
	10.00-20	16	146/142L	TT	1054	278	15.4	115/790	3000/6610	105/720	2650/5840	7.5
	10.00-20	16HD*	146/142J	TT	1054	278	15.4	115/790	3000/6610	105/720	2650/5840	7.5
	11.00-20	16	150/145L	TT	1085	293	16.8	115/790	3350/7390	105/720	2900/6395	8.0
D109	10.00-20	16	146/142L	TT	1054	278	15.9	115/790	3000/6610	105/720	2650/5840	7.5

*HD : Heavy Duty

**D110****DSS111****D201****D202****D204****D205**

PATTERN NAME	SIZE	PLY RATING	LI/SS	TYPE	INFLATED DIMENSION		TREAD DEPTH mm	INFLATION PRESSURE SINGLE PSI/kPa	MAX. LOAD SINGLE kgs/lbs	INFLATION PRESSURE DUAL PSI/kPa	MAX. LOAD DUAL kgs/lbs	RIM WIDTH inch
					OD (mm)	SW (mm)						
D110	10.00-20	16	146/142L	TT	1054	278	15.8	115/790	3000/6610	105/720	2650/5840	7.5
DSS111	10.00-20	16	146/142L	TT	1054	278	16.0	115/790	3000/6610	105/720	2650/5840	7.5
D201	9.00-20	14	141/137L	TT	1019	259	16.1	110/760	2575/5675	100/690	2300/5070	7.0
	10.00-20	16	146/142L	TT	1054	278	17.7	115/790	3000/6610	105/720	2650/5840	7.5
	11.00-20	16	150/145L	TT	1085	293	17.7	115/790	3350/7390	105/720	2900/6395	8.0
		18	152/147L	TT	1085	293	17.7	125/860	3550/7830	115/790	3075/6780	8.0
	12.00-20	18	154/150L	TT	1125	315	17.7	115/790	3750/8270	105/720	3350/7390	8.5
D202	8.25-20	14	136/132L	TT	982	236	15.0	115/790	2240/4940	105/720	2000/4410	6.5
	9.00-20	14	141/137L	TT	1019	259	17.7	110/760	2575/5675	100/690	2300/5070	7.0
		16	144/140L	TT	1019	259	17.7	125/860	2800/6175	115/790	2500/5510	7.0
D204	9.00-20	14	141/137L	TT	1019	259	15.0	110/760	2575/5675	100/690	2300/5070	7.0
	10.00-20	16	146/142L	TT	1054	278	15.0	115/790	3000/6610	105/720	2650/5840	7.5
D205	10.00-20	16	146/142L	TT	1054	278	19.7	115/790	3000/6610	105/720	2650/5840	7.5
	11.00-20	16	150/145L	TT	1085	293	17.7	115/790	3350/7390	105/720	2900/6395	8.0
		18	152/147L	TT	1085	293	17.3	125/860	3550/7830	115/790	3075/6780	8.0

**D206****D207****D208****D209****D325**

PATTERN NAME	SIZE	PLY RATING	LI/SS	TYPE	INFLATED DIMENSION		TREAD DEPTH mm	INFLATION PRESSURE SINGLE PSI/kPa	MAX. LOAD SINGLE kgs/lbs	INFLATION PRESSURE DUAL PSI/kPa	MAX. LOAD DUAL kgs/lbs	RIM WIDTH inch
					OD (mm)	SW (mm)						
D206	10.00-20	18	149/145L	TT	1067	278	21.6	130/900	3250/7160	120/830	2900/6395	7.5
D207	10.00-20	16	146/142L	TT	1073	278	22.6	115/790	3000/6610	105/720	2650/5840	7.5
		16 HD*	149/145J	TT	1073	278	22.6	115/790	3000/6610	105/720	2650/5840	7.5
		18	149/145L	TT	1073	278	22.6	130/900	3250/7160	120/830	2900/6395	7.5
		18 HD*	149/145L	TT	1073	278	22.6	130/900	3250/7160	120/830	2900/6395	7.5
	11.00-20	18	152/147L	TT	1140	293	24.0	125/860	3250/7160	115/790	3350/7830	8.0
		20	154/149L	TT	1140	293	24.0	130/900	3250/7160	120/830	3750/8270	8.0
D208	10.00-20	16	146/142L	TT	1073	278	21.1	115/790	3000/6610	105/720	2650/5840	7.5
D209	10.00-20	16	146/142L	TT	1067	278	21.1	115/790	3000/6610	105/720	2650/5840	7.5
		16 HD*	146/142J	TT	1067	278	21.1	115/790	3000/6610	105/720	2650/5840	7.5
		18	149/145L	TT	1067	278	21.1	130/900	3250/7160	120/830	2900/6395	7.5
		18 HD*	149/145J	TT	1067	278	21.1	130/900	3250/7160	120/830	2900/6395	7.5
D325	12.00-24	18	158/154G	TT	1275	315	36.0	115/790	4250/9370	105/720	3750/8270	8.5

*HD : Heavy Duty

LIGHT TRUCK





D102

D108

D112

D201

PATTERN NAME	SIZE	PLY RATING	LI/SS	TYPE	INFLATED DIMENSION		TREAD DEPTH mm	INFLATION PRESSURE SINGLE PSI/kPa	MAX. LOAD SINGLE kgs/lbs	INFLATION PRESSURE DUAL PSI/kPa	MAX. LOAD DUAL kgs/lbs	RIM WIDTH inch
					OD (mm)	SW (mm)						
D102	7.00-15	10	110/105L	TT	752	202	11.5	80/550	1060/2335	80/550	925/2040	5.5
		12	114/112L	TT	752	202	11.5	83/575	1180/2600	83/575	1120/2470	5.5
	7.50-15	12	120/118L	TT	780	211	12.0	87/600	1400/3085	87/600	1320/2910	6.0
		14	121/119L	TT	780	211	12.0	95/660	1450/3195	95/660	1360/3000	6.0
	6.50-16	12	111/106L	TT	755	182	12.0	95/660	1090/2400	95/660	950/2090	4.5
	7.00-16	12	116/114L	TT	776	194	12.0	83/575	1250/2755	83/575	1180/2600	5.5
		14	118/116L	TT	776	194	12.0	94/625	1320/2910	94/625	1250/2755	5.5
	7.50-16	12	121/119L	TT	808	220	12.0	87/600	1450/3195	87/600	1360/3000	6.0
		14	122/121L	TT	808	220	12.0	95/660	1500/3305	95/660	1450/3195	6.0
		14HD*	122/121G	TT	808	220	12.0	95/660	1500/3305	95/660	1450/3195	6.0
8.25-16	14	126/124L	TT	854	234	12.0	110/760	1600/3525	110/760	1500/3310	6.0	
D108	7.00-16	12	116/114L	TT	776	194	12.0	83/575	1250/2755	83/575	1180/2600	5.5
	7.50-16	12	121/119L	TT	808	220	12.3	87/600	1450/3195	87/600	1360/3000	6.0
		14HD*	122/121G	TT	808	220	12.3	95/660	1500/3305	95/660	1450/3195	6.0
	8.25-16	14	126/124L	TT	854	234	12.0	85/590	1700/3750	85/590	1600/3525	6.5
D112	9.00-16	8	199N	TL	860	274	9.0	45/310	1360/2995	-	-	8.0
D201	7.00-15	12	114/112L	TT	752	202	11.5	83/575	1180/2600	83/575	1120/2470	5.5
		12	120/118L	TT	780	211	12.0	87/600	1400/3085	87/600	1320/2910	6.0
	7.50-15	14	121/119L	TT	780	211	12.0	95/660	1450/3195	95/660	1360/3000	6.0
		16	123/121L	TT	780	211	12.0	110/760	1550/3415	110/760	1450/3195	6.0
	7.00-16	12	116/114L	TT	776	194	12.0	83/575	1250/2755	83/575	1180/2600	5.5
		14	118/116L	TT	776	194	12.0	94/650	1320/2910	94/650	1250/2755	5.5
	7.50-16	14	122/121L	TT	808	220	12.0	95/660	1500/3305	95/660	1450/3195	6.0
	8.25-16	14	126/124L	TT	854	234	12.5	85/590	1700/3750	85/590	1600/3525	6.5

*HD : Heavy Duty



D207

D502

D503

D506

D902

D903

PATTERN NAME	SIZE	PLY RATING	LI/SS	TYPE	INFLATED DIMENSION		TREAD DEPTH mm	INFLATION PRESSURE SINGLE PSI/kPa	MAX. LOAD SINGLE kgs/lbs	INFLATION PRESSURE DUAL PSI/kPa	MAX. LOAD DUAL kgs/lbs	RIM WIDTH inch	
					OD (mm)	SW (mm)							
D207	7.50-16	14HD*	122/121C	TT	819	220	16.5	95/660	1500/3305	95/660	1450/3195	6.0	
D502	6.00-16	6	96/94L	TT	728	166	12.9	47/325	710/1565	47/325	670/1475	4.5	
		8	101/99L	TT	728	166	12.9	60/415	825/1820	60/415	775/1710	4.5	
D503	7.00-15	8	105/101L	TT	752	202	12.5	65/450	925/2040	65/450	825/1820	5.5	
		8	105/101L	TL	752	202	12.5	65/450	925/2040	65/450	825/1820	5.5	
		10	110/105L	TT	752	202	12.5	80/550	1060/2335	80/550	925/2040	5.5	
		10	110/105L	TL	752	202	12.5	80/550	1060/2335	80/550	925/2040	5.5	
	7.00-16	8	109/107L	TT	776	194	12.5	61/425	1030/2270	61/425	975/2150	5.5	
		8	109/107L	TL	776	194	12.5	61/425	1030/2270	61/425	975/2150	5.5	
		10	112/110L	TT	776	194	12.5	72/500	1120/2470	72/500	1060/2335	5.5	
		10	112/110L	TL	776	194	12.5	72/500	1120/2470	72/500	1060/2335	5.5	
		12	116/114L	TT	776	194	12.5	83/575	1250/2755	83/575	1180/2600	5.5	
		12	116/114L	TL	776	194	12.5	83/575	1250/2755	83/575	1180/2600	5.5	
	7.50-16	14	118/116L	TT	776	194	12.5	94/650	1320/2910	94/650	1250/2755	5.5	
		14	118/116L	TL	776	194	12.5	94/650	1320/2910	94/650	1250/2755	5.5	
		8	112/107L	TT	819	220	14.0	65/450	1120/2470	65/450	975/2150	6.0	
		8	112/107L	TL	819	220	14.0	65/450	1120/2470	65/450	975/2150	6.0	
		10	116/112L	TT	819	220	14.0	80/550	1250/2775	80/550	1120/2470	6.0	
		10	116/112L	TL	819	220	14.0	80/550	1250/2775	80/550	1120/2470	6.0	
		12	121/119L	TT	819	220	14.0	87/600	1450/3195	87/600	1360/3000	6.0	
		12	121/119L	TL	819	220	14.0	87/600	1450/3195	87/600	1360/3000	6.0	
	D506	7.00-16	12	116/114L	TT	776	194	16.5	83/570	1250/2750	83/570	1180/2600	5.5
		7.50-16	12	121/119L	TT	819	220	15.5	87/600	1450/3190	87/600	1360/2990	6.0
14			122/121L	TT	819	220	15.5	95/650	1500/3300	95/650	1450/3190	6.0	
D902	7.00-14	6	89/85L	TT	680	186	8.5	50/345	595/1310	50/345	525/1160	5.5	
	6.70-15	6	95/91L	TT	721	190	8.5	50/345	690/1520	50/345	615/1355	5.0	
		6	99/95L	TL	752	202	9.1	45/310	775/1710	45/310	690/1520	5.5	
	7.00-15	8	105/101L	TL	752	202	9.1	65/450	925/2040	65/450	825/1820	5.5	
		10	110/105L	TL	752	202	9.1	75/520	1060/2335	75/520	925/2040	5.5	
	ST205/90D15 (7.00-15)	14	118/115L	TL	752	220	9.1	105/720	1320/2910	105/720	1215/2680	5.5	
	6.50-16	6	97/93L	TT	755	183	8.5	50/345	730/1610	50/345	650/1435	4.5	
		7.50-16	8	112/107L	TL	808	220	9.4	65/450	1120/2470	65/450	975/2150	6.0
			10	116/112L	TL	808	220	9.4	75/520	1250/2755	75/520	1120/2470	6.0
		ST225/90D16 (7.50-16)	14	123/120L	TL	808	220	9.4	105/720	1550/3415	105/720	1400/3085	6.0
	8.00-16.5	10	110/105L	TL	720	203	10.8	75/520	1060/2335	75/520	925/2040	6.0	
		8.75-16.5	8	111/106L	TL	748	222	10.8	65/450	1090/2405	65/450	950/2095	6.75
10			115/111L	TL	748	222	10.8	80/550	1215/2680	80/550	1090/2405	6.75	
9.50-16.5		8	117/112L	TL	776	241	11.3	65/450	1285/2835	65/450	1120/2740	6.75	
		10	121/117L	TL	776	241	11.3	80/550	1450/3195	80/550	1285/2835	6.75	
D903		7.50-16	8	112/107L	TT	808	220	11.0	65/450	1120/2470	65/450	975/2150	6.0
	12		121/119L	TT	808	220	11.0	87/600	1450/3195	87/600	1360/3000	6.0	

ULTRA LIGHT TRUCK



**D96****D100****D102****D108**

PATTERN NAME	SIZE	PLY RATING	LI/SS	TYPE	INFLATED DIMENSION		TREAD DEPTH mm	INFLATION PRESSURE SINGLE PSI/kPa	MAX. LOAD SINGLE kgs/lbs	INFLATION PRESSURE DUAL PSI/kPa	MAX. LOAD DUAL kgs/lbs	RIM WIDTH inch
					OD (mm)	SW (mm)						
D96	145-10	6	76M	TL	505	147	6.5	50/345	400/880	-	-	3.5
		8	83M	TL	505	147	6.5	58/400	485/1070	-	-	3.5
D100	5.00-10	8	79/77L	TT	517	137	7.9	58/400	437/963	58/400	412/908	3.5
		10	83/81L	TL	517	137	7.9	62/425	487/1075	62/425	462/1020	3.5
D102	6.00-9	10	95L	TT	543	175	8.6	100/690	685/1510	-	-	4.5
	5.00-12	10	88/86L	TT	568	137	8.3	75/515	560/1230	75/515	530/1160	3.5
	6.00-13	10	99/97L	TT	653	166	8.7	72/500	780/1720	72/500	743/1640	4.5
	6.00-14	8	98/96L	TT	678	166	12.0	62/425	750/1650	62/425	710/1570	4.5
	6.50-14	8	102/100L	TT	702	175	11.0	62/425	840/1850	62/425	795/1750	4.5
		10	105/103L	TT	702	175	11.0	72/500	925/2040	72/500	875/1930	4.5
D108	7.50-14	8	102/100L	TT	755	206	9.4	62/425	840/1850	62/425	800/1765	6.0



D201

D206

D502

D504

PATTERN NAME	SIZE	PLY RATING	LI/SS	TYPE	INFLATED DIMENSION		TREAD DEPTH mm	INFLATION PRESSURE SINGLE PSI/kPa	MAX. LOAD SINGLE kgs/lbs	INFLATION PRESSURE DUAL PSI/kPa	MAX. LOAD DUAL kgs/lbs	RIM WIDTH inch
					OD (mm)	SW (mm)						
D201	6.00-13	10	99/98L	TT	653	166	9.0	72/500	780/1720	72/500	743/1640	4.5
	6.00-14	8	98/96L	TT	678	166	9.0	62/425	750/1655	62/425	710/1565	4.5
	6.50-14	8	102/100L	TT	702	175	11.9	62/425	840/1850	62/425	795/1750	4.5
		10	105/103L	TT	702	175	11.9	72/500	925/2040	72/500	875/1930	4.5
D206	5.00-12	12	94/92L	TT	568	137	9.5	88/585	670/1480	85/585	630/1390	3.5
D502	6.40/6.50-13	6	85L	TT	633	169	12.9	36/250	515/1135	-	-	5.0
		8	90L	TT	633	169	12.9	47/325	600/1320	-	-	5.0
D504	5.00-12	10	88/86L	TT	568	137	9.3	75/515	560/1230	75/515	530/1160	3.5
		12	94/92L	TT	568	137	9.3	85/585	670/1480	85/585	630/1390	3.5

MILITARY



**D501****D505**

PATTERN NAME	SIZE	PLY RATING	LI/SS	TYPE	INFLATED DIMENSION		TREAD DEPTH mm	INFLATION PRESSURE SINGLE PSI/kPa	MAX. LOAD SINGLE kgs/lbs	INFLATION PRESSURE DUAL PSI/kPa	MAX. LOAD DUAL kgs/lbs	RIM WIDTH inch
					OD (mm)	SW (mm)						
D501	6.00-16	6	96/94L	TT	728	166	12.9	47/325	710/1565	47/325	670/1475	4.5
	7.50-20	8	121/166L	TT	952	215	14.0	75/520	1450/3195	65/450	1250/2755	6.0
	9.00-20	12	138/133L	TT	1038	259	16.3	95/660	2360/5205	85/590	2060/4540	7.0
D505	12.5-20	12	132G	TL	1040	325	16.7	62/425	2000/4410	-	-	11.0

TRAILER



**D95****D268****D269****D292****D622**

PATTERN NAME	SIZE	PLY RATING	LI/SS	TYPE	INFLATED DIMENSION		TREAD DEPTH mm	INFLATION PRESSURE SINGLE		MAX. LOAD SINGLE kgs/lbs	INFLATION PRESSURE DUAL		MAX. LOAD DUAL kgs/lbs	RIM WIDTH inch
					OD (mm)	SW (mm)		PSI/kPa	PSI/kPa					
D95	4.80-8	6	71J	TT	423	121	4.7	90/620	345/760	-	-	-	-	3.75
		8	76E	TT	423	121	4.7	90/620	400/880	-	-	-	-	3.75
D268	16.5x6.50-8	4	64J	TL	411	165	3.9	45/310	280/615	-	-	-	-	5.375
		6	72J	TL	411	165	3.9	70/480	355/785	-	-	-	-	5.375
	18.5x8.50-8	4	71J	TL	462	213	5.5	35/250	345/760	-	-	-	-	7.0
		6	78J	TL	462	213	5.5	50/340	425/935	-	-	-	-	7.0
	20.5x8.0-10	12	90J	TL	462	213	5.5	92/630	600/1325	-	-	-	-	7.0
		4	77J	TL	518	203	6.2	35/250	412/910	-	-	-	-	6.0
		6	84J	TL	518	203	6.2	50/340	500/1100	-	-	-	-	6.0
		8	90J	TL	518	203	6.2	70/480	600/1320	-	-	-	-	6.0
10		95J	TL	518	203	6.2	90/620	690/1520	-	-	-	-	6.0	
12		99J	TL	518	203	6.2	110/760	775/1710	-	-	-	-	6.0	
D269	5.00-8	6	90F	TT	469	146	4.7	87/600	600/1320	-	-	-	-	4.0
		8	126F	TT	469	146	4.7	38/360	1700/3750	-	-	-	-	4.0
	6.00-9	8	126A2	TT	545	160	4.8	100/690	1700/3750	-	-	-	-	4.0
		10	134A2	TT	545	160	4.8	110/760	2120/4670	-	-	-	-	4.0
		12	143A2	TT	545	160	4.8	130/900	2725/6005	-	-	-	-	4.0
D292	7-14.5	8	102J	TL	677	185	5.5	70/480	850/1875	-	-	-	-	6.0
		12	110J	TL	677	185	5.5	100/690	1060/2335	-	-	-	-	6.0
	8-14.5	10	114J	TL	707	203	6.3	85/590	1180/2600	-	-	-	-	6.0
		12	117J	TL	707	203	6.3	100/690	1285/2835	-	-	-	-	6.0
		14	120J	TL	707	203	6.3	115/790	1400/3085	-	-	-	-	6.0
		10	114J	TL	707	203	6.3	85/590	1180/2600	-	-	-	-	6.0
205/75D14.5	14	120J	TL	707	203	6.3	115/790	1400/3085	-	-	-	-	6.0	
D622	ST165/80D13 (A78-13)	4	80/76L	TL	594	165	6.2	35/250	450/990	35/250	400/880	4.5		
		6	88/83L	TL	594	165	6.2	50/350	560/1230	50/350	487/1070	4.5		
	ST175/80D13 (B78-13)	4	84/79L	TL	610	177	7.6	35/250	500/1100	35/250	437/965	5.0		
		6	91/87L	TL	610	177	7.6	50/350	615/1360	50/350	545/1200	5.0		
	ST185/80D13 (C78-13)	4	87/82L	TL	626	184	7.0	35/250	545/1200	35/250	475/1050	5.0		
		6	94/89L	TL	626	184	7.0	50/350	670/1480	50/350	580/1280	5.0		
		8	99/95L	TL	626	184	7.0	65/450	775/1710	65/450	690/1520	5.0		
	ST195/75D14 (E78-14)	4	90/86L	TL	648	196	7.7	35/250	600/1320	35/250	530/1170	5.5		
		6	97/93L	TL	648	196	7.7	50/350	730/1610	50/350	650/1430	5.5		
		8	102/98L	TL	648	196	7.7	65/450	850/1875	65/450	750/1655	5.5		
	ST205/75D14 (F78-14)	4	93/89L	TL	664	203	7.8	35/250	650/1430	35/250	580/1280	5.5		
		6	100/96L	TL	664	203	7.8	50/350	800/1760	50/350	710/1570	5.5		
	ST205/75D15 (F78-15)	4	94/89L	TL	689	203	9.0	35/250	670/1480	35/250	580/1280	5.5		
		6	101/97L	TL	689	203	9.0	50/350	825/1820	50/350	730/1610	5.5		
	ST225/75D15 (H78-15)	6	107/102L	TL	719	223	9.1	50/350	975/2150	50/350	850/1870	6.0		
8		113/108L	TL	719	223	9.1	65/450	1150/2540	65/450	1000/2200	6.0			



D8034

D901

D902

D905

PATTERN NAME	SIZE	PLY RATING	LI/SS	TYPE	INFLATED DIMENSION		TREAD DEPTH	INFLATION PRESSURE SINGLE	MAX. LOAD SINGLE	INFLATION PRESSURE DUAL	MAX. LOAD DUAL	RIM WIDTH	
					OD (mm)	SW (mm)	mm	PSI/kPa	kgs/lbs	PSI/kPa	kgs/lbs	inch	
D8034	16.5x6.50-8	4	64J	TL	411	165	5.5	45/310	280/615	-	-	5.375	
		6	72J	TL	411	165	5.5	70/480	355/785	-	-	5.375	
	18.5x8.50-8	4	71J	TL	462	213	5.5	35/250	345/760	-	-	7.0	
		6	78J	TL	462	213	5.5	50/340	425/935	-	-	7.0	
	20.5x8.0-10	4	77J	TL	518	203	7.9	35/250	412/910	-	-	6.0	
			6	84J	TL	518	203	7.9	50/340	500/1100	-	-	6.0
		8	90J	TL	518	203	7.9	70/480	600/1320	-	-	6.0	
			10	95J	TL	518	203	7.9	90/620	690/1520	-	-	6.0
12		99J	TL	518	203	7.9	110/760	775/1710	-	-	6.0		
D901	4.80-8	4	62J	TL	423	121	5.5	60/410	265/585	-	-	3.75	
		6	71J	TL	423	121	5.5	90/620	345/760	-	-	3.75	
	5.70-8	4	69J	TL	469	146	6.3	50/340	325/715	-	-	4.5	
		6	77J	TL	469	146	6.3	75/520	412/910	-	-	4.5	
	8	83J	TL	469	146	6.3	100/690	487/1070	-	-	4.5		
	5.00-10	4	69/67J	TL	517	137	8.7	35/250	325/715	35/240	307/676	3.5	
		6	74/72J	TL	517	137	8.7	43/300	375/826	43/300	355/782	3.5	
	8	79/77J	TL	517	137	8.7	58/400	437/963	58/400	412/908	3.5		
	4.80-12	4	72J	TL	524	121	5.5	60/410	355/785	-	-	3.75	
		6	80J	TL	524	121	5.5	90/620	450/990	-	-	3.75	
	5.00-12	8	83/81J	TL	568	137	5.5	58/400	487/1075	58/400	462/1020	4.25	
		4	75J	TL	548	135	5.5	55/380	387/855	-	-	4.25	
	5.30-12	6	82J	TL	548	135	5.5	80/550	475/1050	-	-	4.25	
		8	87J	TL	548	135	5.5	100/690	545/1200	-	-	4.25	
	ST175/80D13 (B78-13)	4	84/79L	TL	610	177	7.9	35/250	500/1100	35/250	437/965	5.0	
		6	91/87L	TL	610	177	7.9	50/350	615/1360	50/350	545/1200	5.0	
ST215/75D14 (G78-14)	4	95/90L	TL	678	216	8.7	35/250	690/1520	35/250	600/1320	6.0		
	6	102/98L	TL	678	216	8.7	50/350	850/1875	50/350	750/1650	6.0		
ST225/75D15 (H78-15)	6	107/102L	TL	719	223	9.5	50/350	975/2150	50/350	850/1870	6.0		
	8	113/108L	TL	719	223	9.5	65/450	1150/2540	65/450	1000/2200	6.0		
D902	7-14.5	8	102/97J	TL	677	185	8.6	70/480	850/1875	70/480	730/1610	6.0	
	8-14.5	12	117/112J	TL	707	203	8.6	100/690	1285/2835	100/690	1120/2470	6.0	
	9-14.5	12	122/117J	TL	711	241	8.6	100/690	1500/3305	100/690	1285/2835	7.0	
		14	125/120J	TL	711	241	8.6	115/790	1650/3640	115/790	1400/3085	7.0	
	7.50-15	12	122/117L	TT	808	215	12.0	105/720	1500/3305	95/660	1285/2835	6.0	
		14	124/120L	TT	808	215	12.0	120/830	1600/3525	110/760	1400/3085	6.0	
	16	126/122L	TT	808	215	12.0	125/860	1700/3745	115/790	1500/3305	6.0		
		14	129/125L	TT	847	236	11.4	115/790	1850/4080	105/720	1650/3640	6.5	
	8.25-15	16	132/127L	TT	847	236	11.4	130/900	2000/4410	120/830	1750/3860	6.5	
		18	134/130L	TT	847	236	11.4	130/900	2120/4670	120/830	1900/4190	6.5	
	9.00-15	12	131/127L	TT	892	259	13.5	95/660	1950/4300	85/590	1750/3860	7.0	
		14	135/130L	TT	892	259	13.5	110/760	2180/4805	100/690	1900/4190	7.0	
	14	137/133L	TT	927	278	13.5	100/690	2300/5070	90/620	2060/4540	7.5		
		16	141/136L	TT	927	278	13.5	115/790	2575/5675	105/720	2240/4940	7.5	
	10.00-15	18	142/137L	TT	927	278	13.5	115/790	2650/5840	105/720	2300/5070	7.5	
	D905	12-16.5	12	129/125L	TL	818	307	14.2	75/520	1850/4080	75/520	1650/3640	9.75
			14	133/128L	TL	818	307	14.2	90/620	2060/4540	90/620	1800/3970	9.75





DEESTONE LIMITED

84 Soi Sinprasong, Moo 7, Petchkasem Road,
Oamnoi, Krathumban, Samutsakhon 74130 Thailand
Tel : [+662]420 0038, 023 4756 Fax : [+662]420 5680

Email : global-business@deestone.com

Website : www.deestone.com