

MOTORCYCLE CATALOG



DEESTONE

MOVE THE WORLD

ABOUT **DEESTONE**

DEESTONE was founded in 1977 by Mr. Suvit Vongsariyavanich. The company's vision is to manufacture quality tires for vehicles. Deestone's business philosophy "Integrity, Honesty, and Accountability" have resulted our company with worldwide reputation, qualifies with the global standards and trusted by more than 120 countries. With over 40 years of experience Deestone has been producing quality tires, while continuously developing every product to the highest standard. The use of new technology has allowed Deestone to create innovations that it meets specific application and use, which answers market demand. Deestone also concerns about environmental factors making our company environmental friendly. We ensure that all of our standard certification is up-to-date. All of our goals are to make our customers trust and proud when using our products.

All products of company serves various market demand which consist of high standard of production and certified with global standards. Deestone Group offers the after sales service to customers, with social responsibilities and warranty on the quality of company's products through all channel of communication with completely and clearly information. Product and brand image have been developing for highest customer satisfaction. We develop and produce quality tires for all segments of vehicles to be a part of your journey.





CONTENT

ABOUT US	02
ON ROAD STANDARD TIRE	04
ON ROAD SPORT TIRE / AUTOMATIC BIKE TIRE	12
ON & OFF ROAD TIRE	16
OFF ROAD TIRE	19
SCOOTER TIRE	21
HEAVY DUTY TIRE	26
INNER TUBE	28
SAFETY INFORMATION	30

ON ROAD STANDARD TIRE

**D727****D747****D767****D776****D777****D780**

PATTERN NAME	SIZE	LI/SS	PR	TYPE	RIM (inch)		INFLATION		MAX. LOAD kg/lbs.	DIMENSION (mm)		TREAD DEPTH (mm)
					RECOM	ALTER	kPa	PSI		OD	SW	
D727	2.25-17	33L	4	TT	1.60	1.40	230	33	115/254	556	61	3.5
D747	2.50-17	38L	4	TT	1.60	1.40	230	33	132/290	568	65	4.0
	2.50-18	40L	4	TT	1.60	1.40	230	33	140/310	593	65	4.0
	2.75-18	42P	4	TT	1.85	1.60	230	33	150/330	613	75	4.0
	3.00-18	47P	4	TT	1.85	1.60/2.15	230	33	175/385	627	80	5.0
		52P	6	TT	1.85	1.60/2.15	280	41	200/440	627	80	5.0
	3.50-18	56P	4	TT	2.15	1.85/2.50	230	33	224/495	649	93	5.0
D767	3.00-16	43P	4	TT	1.85	1.60/2.15	230	33	155/340	576	80	5.0
	2.50-17	38L	4	TT	1.60	1.40	230	33	132/290	568	65	4.0
		43L	6	TT	1.60	1.40	280	41	155/340	568	65	4.0
	3.00-17	45P	4	TT	1.85	1.60/2.15	230	33	165/365	602	80	5.0
		45P	4	TL	1.85	1.60/2.15	230	33	165/365	602	80	5.0
	2.50-18	40L	4	TT	1.60	1.40	230	33	140/310	593	65	5.2
		45L	6	TT	1.60	1.40	280	41	165/365	593	65	5.2
	2.75-18	42P	4	TT	1.85	1.60	230	33	150/330	613	75	5.2
		42P	4	TL	1.85	1.60	230	33	150/330	613	75	5.2
		48P	6	TT	1.85	1.60	280	41	180/395	613	75	5.2
		48P	6	TL	1.85	1.60	280	41	180/395	613	75	5.2
	3.00-18	47P	4	TT	1.85	1.60/2.15	230	33	175/385	627	80	5.0
		47P	4	TL	1.85	1.60/2.15	230	33	175/385	627	80	5.0
D776	2.25-17	33L	4	TT	1.60	1.40	230	33	115/254	556	61	5.0
	2.25-19	32L	2	TT	1.60	1.40	175	25	112/247	607	61	4.0
		37L	4	TT	1.60	1.40	230	33	128/280	607	61	4.0
	2.50-19	41L	4	TT	1.60	1.40	230	33	145/320	619	65	5.0
D777	2.75-14	35P	4	TT	1.85	1.60	230	33	121/267	512	75	5.0
		41P	6	TT	1.85	1.60	280	41	145/320	512	75	5.0
	2.50-17	38L	4	TT	1.60	1.40	230	33	132/290	568	65	5.0
		43L	6	TT	1.60	1.40	280	41	155/340	568	65	5.0
	2.75-17	41P	4	TT	1.85	1.60	230	33	145/320	588	75	5.0
		47P	6	TT	1.85	1.60	280	41	175/385	588	75	5.0
	2.50-18	40L	4	TT	1.60	1.40	230	33	140/310	593	65	5.5
	2.75-18	42P	4	TT	1.85	1.60	230	33	150/330	613	75	6.5
		48P	6	TT	1.85	1.60	280	41	180/395	613	75	6.5
D780	3.00-18	47P	4	TT	1.85	1.60/2.15	230	33	175/385	627	80	5.5
		52P	6	TT	1.85	1.60/2.15	280	41	200/440	627	80	5.5

**D85****D778****D781****D968****D969****D973**

PATTERN NAME	SIZE	LI/SS	PR	TYPE	RIM (inch)		INFLATION		MAX. LOAD kg/lbs.	DIMENSION (mm)		TREAD DEPTH (mm)
					RECOM	ALTER	kPa	PSI		OD	SW	
D85	2.25-17	33L	4	TT	1.60	1.40	230	33	115/254	556	61	3.5
		38L	6	TT	1.60	1.40	280	41	132/290	556	61	3.5
	2.50-17	38L	4	TT	1.60	1.40	230	33	132/290	568	65	3.5
		43L	6	TT	1.60	1.40	280	41	155/340	568	65	3.5
D778	2.50-16	36L	4	TT	1.60	1.40	230	33	125/275	542	65	4.0
	3.00-16	43P	4	TT	1.85	1.60/2.15	230	33	155/340	576	80	7.0
	2.50-17	38L	4	TT	1.60	1.40	230	33	132/290	568	65	5.0
	3.00-17	45P	4	TT	1.85	1.60/2.15	230	33	165/365	602	80	7.0
		50P	6	TT	1.85	1.60/2.15	280	41	190/420	602	80	7.0
	2.50-18	40L	4	TT	1.60	1.40	230	33	140/310	593	65	5.0
	2.75-18	42P	4	TT	1.85	1.60	230	33	150/330	613	75	5.0
D781	2.50-17	38L	4	TT	1.60	1.40	230	33	132/290	568	65	4.5
	2.75-17	41P	4	TT	1.85	1.60	230	33	145/320	588	75	5.0
		47P	6	TL	1.85	1.60	280	41	175/385	588	75	5.0
	2.75-18	42P	4	TT	1.85	1.60	230	33	150/330	613	75	5.0
		48P	6	TT	1.85	1.60	280	41	180/395	613	75	5.0
		48P	6	TL	1.85	1.60	280	41	180/395	613	75	5.0
	3.00-18	47P	4	TT	1.85	1.60/2.15	230	33	175/385	627	80	5.0
		52P	6	TT	1.85	1.60/2.15	280	41	200/440	627	80	5.0
		52P	6	TL	1.85	1.60/2.15	280	41	200/440	627	80	5.0
D968	2.1/4-16	31L	4	TT	1.60	1.40	230	33	109/240	532	62	3.5
D969	2.50-17	38L	4	TT	1.60	1.40	230	33	132/290	568	65	4.5
		43L	6	TT	1.60	1.40	280	41	155/340	568	65	4.5
	3.00-17	45P	4	TT	1.85	1.60/2.15	230	33	165/365	602	80	7.0
		50P	6	TT	1.85	1.60/2.15	280	41	190/420	602	80	7.0
		50P	6	TL	1.85	1.60/2.15	280	41	190/420	602	80	7.0
	2.50-18	40L	4	TT	1.60	1.40	230	33	140/310	593	65	4.5
		45L	6	TT	1.60	1.40	280	41	165/365	593	65	4.5
	2.75-18	42P	4	TT	1.85	1.60	230	30	180/395	613	75	5.0
		48P	6	TT	1.85	1.60	280	41	180/395	613	75	5.0
	3.00-18	47P	4	TT	1.85	1.60/2.15	230	33	200/440	627	80	6.0
		52P	6	TT	1.85	1.60/2.15	280	41	200/440	627	80	6.0
D973	2.3/4-16	35P	2	TT	1.85	1.60	175	25	121/267	558	75	5.0
		46P	6	TT	1.85	1.60	280	41	170/375	558	75	5.0

**D782****D789****D793****D795****D796****D797**

PATTERN NAME	SIZE	LI/SS	PR	TYPE	RIM (inch)		INFLATION		MAX. LOAD kg/lbs.	DIMENSION (mm)		TREAD DEPTH (mm)
					RECOM	ALTER	kPa	PSI		OD	SW	
D782	3.00-18	52P	6	TT	1.85	1.60/2.15	280	41	200/440	627	80	3.8
		52P	6	TL	1.85	1.60/2.15	280	41	200/440	627	80	3.8
D789	2.50-17	38L	4	TT	1.60	1.40	230	33	132/290	568	65	4.5
	2.50-18	40L	4	TT	1.60	1.40	230	33	140/310	593	65	4.5
D793	2.25-17	33L	4	TT	1.60	1.40	230	33	115/254	556	61	3.0
	2.50-17	38L	4	TT	1.60	1.40	230	33	132/290	568	65	4.5
		43L	6	TT	1.60	1.40	280	41	155/340	568	65	4.5
D795	2.75-16	40P	4	TT	1.85	1.60	230	33	140/310	562	75	5.0
	2.50-17	38L	4	TT	1.60	1.40	230	33	132/290	568	65	4.0
	2.50-18	40L	4	TT	1.60	1.40	230	33	140/310	593	65	4.0
D796	2.75-18	42P	4	TT	1.85	1.60	230	33	145/320	613	75	4.0
D797	2.50-17	38L	4	TT	1.60	1.40	230	33	132/290	568	65	4.0

**D798****D799****D800****D8000****D801****D802**

PATTERN NAME	SIZE	LI/SS	PR	TYPE	RIM (Inch)		INFLATION		MAX. LOAD kg/lbs.	DIMENSION (mm)		TREAD DEPTH (mm)
					RECOM	ALTER	kPa	PSI		OD	SW	
D798	2.25-17	33L	4	TT	1.60	1.40	230	33	115/254	556	61	3.0
	2.50-17	38L	4	TT	1.60	1.40	230	33	132/290	568	65	3.5
D799	2 1/4-17	33L	4	TT	1.60	1.40	230	33	95/209	532	62	3.0
D800	2.25-16	31L	4	TT	1.60	1.40	230	33	109/240	530	61	3.5
	2.50-18	40L	4	TT	1.60	1.40	230	33	140/310	593	65	4.0
D8000	2 1/4-16	26L	2	TT	1.60	1.40	175	25	95/209	532	62	3.5
		31L	4	TT	1.60	1.40	230	33	109/240	532	62	3.5
	2.50-16	36L	4	TT	1.60	1.40	230	33	125/275	542	65	4.0
		42L	6	TT	1.60	1.40	280	41	150/330	542	65	4.0
D801	2.00-17	27L	4	TT	1.20	1.40	230	33	97.5/215	542	52	3.0
	2.25-17	33L	4	TT	1.60	1.40	230	33	115/254	556	61	3.5
	2.50-17	38L	4	TT	1.60	1.40	230	33	132/290	568	65	4.0
	2.50-18	40L	4	TT	1.60	1.40	230	33	140/310	593	65	4.0
D802	2.00-17	27L	4	TT	1.20	1.40	230	33	97.5/215	542	52	3.5
	2.25-17	33L	4	TT	1.60	1.40	230	33	115/254	556	61	3.5
	2.50-17	38L	4	TT	1.60	1.40	230	33	132/290	568	65	4.0
	2.50-18	40L	4	TT	1.60	1.40	230	33	140/310	593	65	5.0
	3.50-18	56P	4	TT	2.15	1.85/2.50	230	33	224/495	649	93	5.0
		56P	4	TL	2.15	1.85/2.50	230	33	224/495	649	93	5.0



PATTERN NAME	SIZE	LI/SS	PR	TYPE	RIM (inch)		INFLATION		MAX. LOAD kg/lbs.	DIMENSION (mm)		TREAD DEPTH (mm)
					RECOM	ALTER	kPa	PSI		OD	SW	
D809	2.25-17	33L	4	TT	1.60	1.40	230	33	115/254	556	61	4.0
	2.50-17	38L	4	TT	1.60	1.40	230	33	132/290	568	65	4.5
	2.75-17	41P	4	TT	1.85	1.60	230	33	145/320	588	75	5.0
D891	2 3/4-16	35P	2	TT	1.85	1.60	175	25	121/267	558	75	5.0
		40P	4	TT	1.85	1.60	230	33	140/310	558	75	5.0
		46P	6	TT	1.85	1.60	280	41	170/375	558	75	5.0
D960	2.00-17	27L	4	TT	1.20	1.40	230	33	97.5/215	542	52	3.0
	2.25-17	33L	4	TT	1.60	1.40	230	33	115/254	556	61	3.5
	2.50-17	38L	4	TT	1.60	1.40	230	33	132/290	568	65	4.0
	2.50-18	40L	4	TT	1.60	1.40	230	33	140/310	593	65	4.0
D961	2.00-17	27L	4	TT	1.20	1.40	230	33	97.5/215	542	52	3.0
	2.25-17	33L	4	TT	1.60	1.40	230	33	115/254	556	61	3.5
	2.50-17	38L	4	TT	1.60	1.40	230	33	132/290	568	65	4.0
	2.50-18	40L	4	TT	1.60	1.40	230	33	140/310	593	65	4.0
D962	2.00-17	27L	4	TT	1.20	1.40	230	33	97.5/215	542	52	3.0
D964	2.00-17	27L	4	TT	1.20	1.40	230	33	97.5/215	542	52	4.0
	2.25-17	33L	4	TT	1.60	1.40	230	33	115/254	556	61	4.0
	2.50-17	38L	4	TT	1.60	1.40	230	33	132/290	568	65	4.5

**D965****D966****D967****D983****D984**

PATTERN NAME	SIZE	LI/SS	PR	TYPE	RIM (inch)		INFLATION		MAX. LOAD kg/lbs.	DIMENSION (mm)		TREAD DEPTH (mm)
					RECOM	ALTER	kPa	PSI		OD	SW	
D965	2.25-17	33L	4	TT	1.60	1.40	230	33	115/254	556	61	4.0
	2.50-17	38L	4	TT	1.60	1.40	230	33	132/290	568	65	4.5
D966	2.00-17	27L	4	TT	1.20	1.40	230	33	97.5/215	542	52	4.0
	2.25-17	33L	4	TT	1.60	1.40	230	33	115/254	556	61	4.0
	2.50-17	38L	4	TT	1.60	1.40	230	33	132/290	568	65	4.5
D967	2.00-17	27L	4	TT	1.20	1.40	230	33	97.5/215	542	52	4.0
	2.25-17	33L	4	TT	1.60	1.40	230	33	115/254	556	61	4.0
	2.50-17	38L	4	TT	1.60	1.40	230	33	132/290	568	65	4.5
		43L	6	TT	1.60	1.40	280	41	155/340	568	65	4.5
	2.75-17	41L	4	TT	1.85	1.60	230	33	145/320	588	75	5.0
		47L	6	TT	1.85	1.60	280	41	175/385	588	75	5.0
D983	60/100-17	33P	4	TT	1.40	1.20	230	33	115/240	552	60	3.0
	70/90-17	38P	4	TT	1.60	1.40	230	33	132/290	558	69	4.0
	80/90-17	44P	4	TT	1.85	1.60	230	33	160/355	576	80	4.5
D984	70/90-17	38P	4	TT	1.60	1.40	230	33	132/290	558	69	4.0
		38P	4	TL	1.60	1.40	230	33	132/290	558	69	4.0
	80/90-17	44P	4	TT	1.85	1.60	230	33	160/355	576	80	4.5
		44P	4	TL	1.85	1.60	230	33	160/355	576	80	4.5

VVV edition



PATTERN NAME	SIZE	LI/SS	PR	TYPE	RIM (inch)		INFLATION		MAX. LOAD	DIMENSION (mm)		TREAD DEPTH (mm)
					RECOM	ALTER	kPa	PSI		OD	SW	
D986	60/100-17	33S	4	TT	1.40	1.20	230	33	115/225	552	60	3.5
	70/90-17	43S	6	TT	1.60	1.40	280	41	155/345	558	69	4.0
	80/90-17	50S	6	TT	1.85	1.60	280	41	190/420	576	80	4.5
	70/90-14	40P	6	TT	1.60	1.40	280	41	140/310	482	69	4.0
	80/90-14	46P	6	TT	1.85	1.60	280	41	170/375	500	80	4.5
		46P	6	TL	1.85	1.60	280	41	170/375	500	80	4.5
	90/90-14	52P	6	TT	2.15	1.85/2.50	280	41	200/440	518	90	5.0
		52P	6	TL	2.15	1.85/2.50	280	41	200/440	518	90	5.0
D987	60/100-17	33S	4	TT	1.40	1.20	230	33	115/225	552	60	3.5
	70/90-17	43S	6	TT	1.60	1.40	280	41	155/345	558	69	4.0
	80/90-17	50S	6	TT	1.85	1.60	280	41	190/420	576	80	4.5
	70/90-14	40P	6	TT	1.60	1.40	280	41	140/310	482	69	4.0
	80/90-14	46P	6	TT	1.85	1.60	280	41	170/375	500	80	4.5
		46P	6	TL	1.85	1.60	280	41	170/375	500	80	4.5
	90/90-14	52P	6	TT	2.15	1.85/2.50	280	41	200/440	518	90	5.0
		52P	6	TL	2.15	1.85/2.50	280	41	200/440	518	90	5.0
D920	2.50-16	41P	6	TT	1.60	1.40	280	41	145/320	542	65	4.0
	2.75-16	46P	6	TT	1.85	1.60	280	41	170/375	562	75	4.5
	2.00-17	30P	6	TT	1.20	1.40	280	41	106/234	542	52	3.0
	2.25-17	38P	6	TT	1.60	1.40	280	41	132/290	556	61	3.5
	2.50-17	43P	6	TT	1.60	1.40	280	41	155/340	568	65	4.0
	2.75-17	47P	6	TT	1.85	1.60	280	41	175/385	588	75	5.0

ON ROAD SPORT TIRE/AUTOMATIC BIKE TIRE

**D792****D803****D804****D822****D963****D970**

PATTERN NAME	SIZE	LI/SS	PR	TYPE	RIM (inch)		INFLATION		MAX. LOAD kg/lbs.	DIMENSION (mm)		TREAD DEPTH (mm)
					RECOM	ALTER	kPa	PSI		OD	SW	
D792	80/100-16	45P	4	TT	1.85	1.60/2.15	230	33	165/365	566	80	5.0
	90/90-18	51P	4	TT	2.15	1.85/2.50	230	33	195/430	619	90	5.0
		51P	4	TL	2.15	1.85/2.50	230	33	195/430	619	90	5.0
D803	50/90-17	27P	4	TT	1.20	1.40	230	33	97.5/215	522	50	3.0
	60/90-17	30P	4	TT	1.40	1.20	230	33	106/234	540	60	4.0
	70/90-17	38P	4	TT	1.60	1.40	230	33	132/290	558	69	4.0
D804	70/90-16	36P	4	TT	1.60	1.40	230	33	125/275	532	69	4.0
	80/90-16	43P	4	TT	1.85	1.60	230	33	155/340	550	80	4.0
	70/90-17	38P	4	TT	1.60	1.40	230	33	132/290	558	69	4.0
	80/90-17	44P	4	TT	1.85	1.60	230	33	160/355	576	80	4.0
D822	70/90-14	34P	4	TT	1.60	1.40	230	33	118/260	482	69	4.0
	80/90-14	40P	4	TT	1.85	1.60	230	33	140/310	500	80	5.6
	70/90-16	36P	4	TT	1.60	1.40	230	33	125/275	532	69	4.0
		36P	4	TL	1.60	1.40	230	33	125/275	532	69	4.0
	80/90-16	43P	4	TT	1.85	1.60	230	33	155/340	550	80	3.5
		43P	4	TL	1.85	1.60	230	33	155/340	550	80	3.5
	70/90-17	38P	4	TT	1.60	1.40	230	33	132/290	558	69	4.5
		38P	4	TL	1.60	1.40	230	33	132/290	558	69	4.5
	80/90-17	44P	4	TT	1.85	1.60	230	33	160/355	576	80	4.1
	90/90-17	49P	4	TL	2.15	1.85/2.50	230	33	185/410	594	90	5.9
	90/80-17	46P	4	TL	2.15	1.85/2.50	230	33	170/375	576	90	5.0
	2.75-18	48P	6	TL	1.85	1.60	280	41	180/395	613	75	5.6
	100/90-18	56S	4	TL	2.50	2.15/2.75	230	33	224/495	637	101	5.6
D963	50/90-17	27P	4	TT	1.20	1.40	230	33	97.5/215	522	50	3.5
	60/90-17	30P	4	TT	1.40	1.20	230	33	106/234	540	60	4.0
D970	50/90-17	27P	4	TT	1.20	1.40	230	33	97.5/215	522	50	3.5
	60/90-17	30P	4	TT	1.40	1.20	230	33	106/234	540	60	3.5
	70/90-17	38P	4	TT	1.60	1.40	230	33	132/290	558	69	4.5

**D971****D972****D975****D976****D977****D978**

PATTERN NAME	SIZE	LI/SS	PR	TYPE	RIM (inch)		INFLATION		MAX. LOAD kg/lbs.	DIMENSION (mm)		TREAD DEPTH (mm)
					RECOM	ALTER	kPa	PSI		OD	SW	
D971	80/80-14	43L	4	TL	1.85	1.60	230	33	155/340	484	80	4.0
	90/80-14	43P	4	TL	2.15	1.85/2.50	230	33	155/340	500	90	5.0
	50/80-17	27L	4	TT	1.20	1.40	230	33	97.5/215	512	52	3.0
	60/80-17	39L	4	TT	1.20	1.40	230	33	136/300	528	60	3.5
	70/80-17	35P	4	TT	1.60	1.40	230	33	121/267	544	69	5.0
	80/80-17	41P	4	TT	1.85	1.60	230	33	145/320	560	80	4.0
	90/80-17	46P	4	TT	2.15	1.85/2.50	230	33	170/375	576	90	5.0
	70/90-17	38P	4	TT	1.60	1.40	230	33	132/290	558	69	4.0
		38P	4	TL	1.60	1.40	230	33	132/290	558	69	4.0
	80/90-17	44P	4	TT	1.85	1.60	230	33	160/355	576	80	4.5
		44P	4	TL	1.85	1.60	230	33	160/355	576	80	4.5
D972	80/80-14	43L	4	TT	1.85	1.60	230	33	155/340	484	80	4.0
D975	70/90-17	38P	4	TT	1.60	1.40	230	33	132/290	558	69	5.0
	60/100-17	33L	4	TT	1.40	1.20	230	33	115/254	552	60	3.0
	70/100-17	40P	4	TT	1.60	1.40	230	33	140/310	572	69	4.5
	2.75-17	41P	4	TT	1.85	1.60	230	33	145/320	588	75	4.0
D976	70/90-17	38P	4	TT	1.60	1.40	230	33	132/290	558	69	5.0
	80/90-17	44P	4	TT	1.85	1.60	230	33	160/355	576	80	4.5
	60/100-17	33L	4	TT	1.40	1.20	230	33	115/254	552	60	3.0
D977	60/90-14	26S	4	TT	1.40	1.20	230	33	95/209	464	60	3.5
	70/90-14	34L	4	TT	1.60	1.40	230	33	118/260	482	69	4.3
		34L	4	TL	1.60	1.40	230	33	118/260	482	69	4.3
	80/90-14	40P	4	TT	1.85	1.60	230	33	140/310	500	80	5.6
		40P	4	TL	1.85	1.60	230	33	140/310	500	80	5.6
	90/90-14	46P	4	TT	2.15	1.85/2.50	230	33	170/375	518	90	5.6
		46P	4	TL	2.15	1.85/2.50	230	33	170/375	518	90	5.6
	45/90-17	19S	4	TT	1.20	1.40	230	33	77.5/171	513	45	3.5
	50/90-17	21S	4	TT	1.20	1.40	230	33	82.5/182	522	50	3.0
	60/90-17	30P	4	TT	1.40	1.20	230	33	106/234	540	60	4.0
D978	70/90-17	38L	4	TT	1.60	1.40	230	33	132/290	558	69	5.0
	80/90-17	44P	4	TT	1.85	1.60	230	33	160/355	576	80	4.5
	50/100-17	23P	4	TT	1.20	1.40	230	33	87.5/193	532	50	3.5
	60/90-17	30P	4	TT	1.40	1.20	230	33	106/234	540	60	4.0
	70/90-17	38P	4	TT	1.60	1.40	230	33	132/290	558	69	5.0
	50/100-17	23P	4	TT	1.20	1.40	230	33	87.5/193	532	50	3.5

**D911****D957****D959****D979****D988****D989**

PATTERN NAME	SIZE	LI/SS	PR	TYPE	RIM (inch)		INFLATION		MAX. LOAD kg/lbs.	DIMENSION (mm)		TREAD DEPTH (mm)
					RECOM	ALTER	kPa	PSI		OD	SW	
D911	60/100-17	33S	4	TT	1.40	1.20	230	33	115/225	552	60	3.5
	70/90-17	38S	4	TT	1.60	1.40	230	33	132/290	558	69	4.0
	80/90-17	44S	4	TT	1.85	1.60	230	33	160/355	576	80	4.5
	70/90-14	34P	4	TT	1.60	1.40	230	33	118/260	482	69	4.0
	80/90-14	40P	4	TT	1.85	1.60	230	33	140/310	500	80	4.5
		40P	4	TL	1.85	1.60	230	33	140/310	500	80	4.5
	90/90-14	46P	4	TT	2.15	1.85/2.50	230	33	170/375	518	90	5.0
		46P	4	TL	2.15	1.85/2.50	230	33	170/375	518	90	5.0
	100/90-14	51P	4	TL	2.50	2.15/2.75	230	33	195/430	536	101	5.5
D957	70/90-17	38P	4	TL	1.60	1.40	230	33	132/290	558	69	4.5
	80/90-17	44P	4	TL	1.85	1.60	230	33	160/355	576	80	5.0
	90/90-18	57P	6	TL	2.15	1.85/2.50	280	41	230/505	619	90	5.0
D959	45/90-17	19S	4	TT	1.20	1.40	230	33	77.5/171	513	45	3.5
	50/90-17	21S	4	TT	1.20	1.40	230	33	82.5/182	522	50	3.5
	60/90-17	30S	4	TT	1.40	1.20	230	33	106/234	540	60	4.0
	70/80-17	35S	4	TT	1.60	1.40	230	33	121/267	544	69	4.0
D979	60/95-17	33P	4	TT	1.40	1.20	230	33	115/254	546	60	3.8
	70/90-17	38P	4	TT	1.60	1.40	230	33	132/290	558	69	4.5
	50/100-17	23P	4	TT	1.20	1.40	230	33	87.5/193	532	50	3.5
D988	70/90-17	38P	4	TT	1.60	1.40	230	33	132/290	558	69	4.0
	80/90-17	44P	4	TT	1.85	1.60	230	33	160/355	576	80	4.5
D989	70/90-17	38P	4	TT	1.60	1.40	230	33	132/290	558	69	4.0
	80/90-17	44P	4	TT	1.85	1.60	230	33	160/355	576	80	4.5

ON & OFF ROAD TIRE

**D707****D775****D779****D790****D903****D904**

PATTERN NAME	SIZE	LI/SS	PR	TYPE	RIM (inch)		INFLATION		MAX. LOAD kg/lbs.	DIMENSION (mm)		TREAD DEPTH (mm)
					RECOM	ALTER	kPa	PSI		OD	SW	
D707	3.50-16	58P	6	TT	2.15	1.85/2.50	280	41	236/520	598	93	8.5
	3.00-17	45P	6	TT	1.85	1.60/2.15	280	41	165/365	602	80	8.5
	3.25-17	50P	4	TT	2.15	1.85/2.50	230	33	190/420	614	89	8.5
	3.50-18	56P	4	TT	2.15	1.85/2.50	230	33	224/495	649	93	9.0
		56P	4	TL	2.15	1.85/2.50	230	33	224/495	649	93	9.0
		62P	6	TT	2.15	1.85/2.50	280	41	265/585	649	93	9.0
D775	110/90-16	65P	6	TL	2.50	2.15/2.75	280	41	290/640	604	109	8.0
	3.00-17	50P	6	TT	1.85	1.60/2.15	280	41	190/420	602	80	8.5
	90/90-18	57P	6	TL	2.15	1.85/2.50	280	41	230/505	619	90	8.0
D779	2.25-17	33L	4	TT	1.60	1.40	230	33	115/254	556	61	6.0
	2.50-17	38L	4	TT	1.60	1.40	230	33	132/290	568	65	6.0
	2.50-18	40L	4	TT	1.60	1.40	230	33	140/310	593	65	6.0
	2.75-18	42P	4	TT	1.85	1.60	230	33	150/330	613	75	7.0
	3.00-18	47P	4	TT	1.85	1.60/2.15	230	33	175/385	627	80	8.0
		47P	4	TL	1.85	1.60/2.15	230	33	175/385	627	80	8.0
		52P	6	TT	1.85	1.60/2.15	280	41	200/440	627	80	8.0
D790	2.75-21	45P	4	TT	1.85	1.60	230	33	165/365	689	75	7.0
D903	110/90-16	59M	4	TT	2.50	2.15/2.75	230	33	243/535	604	109	8.0
		59M	4	TL	2.50	2.15/2.75	230	33	243/535	604	109	8.0
		65M	8	TT	2.50	2.15/2.75	280	41	290/640	604	109	8.0
		65M	8	TL	2.50	2.15/2.75	280	41	290/640	604	109	8.0
	120/90-16	63M	4	TL	2.75	2.50/3.00	230	33	272/600	622	119	10.0
	90/100-19	55M	4	TL	2.15	1.85/2.50	230	33	218/480	663	90	7.5
D904	3.00-18	52P	6	TL	1.85	1.60/2.15	280	41	200/440	627	80	7.0

**D905****D906****D982****D999**

PATTERN NAME	SIZE	LI/SS	PR	TYPE	RIM (inch)		INFLATION		MAX. LOAD kg/lbs.	DIMENSION (mm)		TREAD DEPTH (mm)
					RECOM	ALTER	kPa	PSI		OD	SW	
D905	110/90-16	65P	6	TL	2.50	2.15/2.75	280	41	290/640	604	109	9.5
	100/90-17	61P	6	TL	2.50	2.15/2.75	280	41	257/565	612	101	10.0
D906	2.75-18	48P	6	TL	1.85	1.60/2.15	280	41	180/395	613	75	6.5
D982	2.25-17	33L	4	TT	1.60	1.40	230	33	115/254	556	61	6.0
	2.50-17	38L	4	TT	1.60	1.40	230	33	132/390	568	65	8.0
	2.75-17	41P	4	TT	1.85	1.60	230	33	145/320	588	75	6.8
	4.60-17	62P	6	TT	2.75	2.50/3.00	280	41	265/585	629	111	16.0
D999	110/90-17	60P	4	TT	2.50	2.15/2.75	230	33	250/550	630	109	8.5
	2.50-17	38L	4	TT	1.60	1.40	230	33	132/290	568	65	6.5
	3.00-17	45P	4	TT	1.85	1.60/2.15	230	33	165/365	602	80	7.5
		50P	6	TT	1.85	1.60/2.15	280	41	190/420	602	80	8.5
	3.00-18	47P	4	TL	1.85	1.60/2.15	230	33	175/385	627	80	8.5
		52P	6	TT	1.85	1.60/2.15	280	41	200/440	627	80	8.5
	4.10-18	64P	4	TT	2.50	2.15/2.75	230	33	280/615	641	108	8.5
		70P	6	TT	2.50	2.15/2.75	280	41	335/740	641	108	8.0
	90/90-19	52P	4	TL	2.15	1.85/2.50	230	33	200/440	645	90	8.0
	2.75-21	45P	4	TT	1.85	1.60/2.15	230	33	165/365	689	75	8.0

OFF ROAD TIRE

**D981****D991****D992**

PATTERN NAME	SIZE	LI/SS	PR	TYPE	RIM (inch)		INFLATION		MAX. LOAD	DIMENSION (mm)		TREAD DEPTH (mm)
					RECOM	ALTER	kPa	PSI		OD	SW	
D981	70/100-17	46M	6	TT	1.60	1.40	280	41	170/375	572	69	9.0
	80/100-21	51M	4	TT	1.85	1.60/2.15	230	33	195/430	693	80	11.5
		57M	6	TT	1.85	1.60/2.15	280	41	230/505	693	80	11.5
D991	90/100-14	49M	6	TT	2.15	1.85/2.50	280	41	185/410	536	90	13.5
	100/100-18	59M	6	TT	2.50	2.15/2.75	280	41	243/535	657	101	15.0
	110/100-18	64M	6	TT	2.50	2.15/2.75	280	41	280/615	677	109	15.0
	120/100-18	68M	6	TT	2.75	2.50/3.00	280	41	315/695	697	119	15.5
	100/90-19	57M	6	TT	2.50	2.15/2.75	280	41	230/505	663	101	16.0
	110/90-19	62M	6	TT	2.50	2.15/2.75	280	41	265/585	681	109	16.0
	120/90-19	66M	6	TT	2.75	2.50/3.00	280	41	300/660	724	119	11.5
D992	120/90-18	65R	6	TT	2.75	2.50/3.00	280	41	290/640	673	119	13.0
	140/80-18	70R	6	TT	3.50	3.00/3.75	280	41	335/740	681	142	13.0
	90/90-21	54P	6	TT	2.15	1.85/2.50	280	41	212/465	695	90	11.0

SCOOTER TIRE

**D7020****D7024****D794****D795****D8001****D801****D806****D807**

PATTERN NAME	SIZE	LI/SS	PR	TYPE	RIM (inch)		INFLATION		MAX. LOAD	DIMENSION (mm)		TREAD DEPTH (mm)
					RECOM	ALTER	kPa	PSI		OD	SW	
D7020	120/90-10	66L	4	TL	2.75	2.50/3.00	250	36	300/660	470	119	4.5
	130/90-10	70L	4	TL	3.00	2.75/3.00	250	36	335/740	488	129	4.5
D7024	130/90-10	70L	4	TL	3.00	2.75/3.00	250	36	335/740	488	129	10.0
D794	3.00-8	38J	4	TL	2.15	1.85/2.50	250	36	132/290	362	80	5.0
D795	3.00-8	26J	2	TT	2.15	1.85/2.50	175	25	132/290	362	80	5.0
		38J	4	TT	2.15	1.85/2.50	250	36	132/290	362	80	5.0
		43J	6	TT	2.15	1.85/2.50	300	44	155/340	362	80	5.0
	3.00-10	42J	4	TT	2.15	1.85/2.50	250	36	150/330	413	80	5.0
		49J	6	TT	2.15	1.85/2.50	300	44	185/410	413	80	5.0
	3.50-10	51J	4	TT	2.50	2.15/2.75	250	36	195/430	437	92	5.5
		51J	4	TL	2.50	2.15/2.75	250	36	195/430	437	92	5.5
D8001	90/90-10	50L	4	TL	2.15	1.85/2.50	250	36	190/420	416	90	5.0
	100/90-10	56L	4	TL	2.50	2.15/2.75	250	36	224/495	434	101	5.5
D801	3.00-10	42J	4	TL	2.15	1.85/2.50	250	36	150/330	413	80	5.0
	3.50-10	51J	4	TL	2.50	2.15/2.75	250	36	195/430	437	92	5.0
D806	90/90-10	50L	4	TL	2.15	1.85/2.50	250	36	190/420	416	90	4.0
D807	90/90-10	50L	4	TL	2.15	1.85/2.50	250	36	190/420	416	90	5.8
	100/90-10	56L	4	TL	2.50	2.15/2.75	250	36	224/495	434	101	5.8

**D805****D808****D809****D810****D811**

PATTERN NAME	SIZE	LI/SS	PR	TYPE	RIM (inch)		INFLATION		MAX. LOAD kg/lbs.	DIMENSION (mm)		TREAD DEPTH (mm)
					RECOM	ALTER	kPa	PSI		OD	SW	
D805	120/70-10	54L	4	TL	3.50	3.00/3.75	280	41	212/465	442	122	5.3
	100/80-10	58L	4	TL	2.50	2.15/2.75	280	41	236/520	414	101	5.3
	120/90-10	57M	4	TL	2.75	2.50/3.00	250	36	230/505	470	119	4.6
	130/90-10	61M	4	TL	3.00	2.75/3.50	250	36	257/565	488	129	4.6
	120/70-11	50M	4	TL	3.50	3.00/3.75	250	36	190/420	447	122	5.3
	130/70-11	60M	4	TL	3.50	3.00/3.75	280	41	250/565	461	129	5.3
	110/70-12	47P	4	TL	3.00	2.75/3.50	280	41	175/385	459	110	5.3
	120/70-12	58P	4	TL	3.50	3.00/3.75	280	41	236/520	473	122	5.3
	130/70-12	62P	4	TL	3.50	3.00/3.75	280	41	265/585	487	129	5.3
	140/70-12	65P	4	TL	3.75	3.50/4.00	280	41	290/550	501	139	5.3
	120/80-12	65M	4	TL	2.75	2.50/3.00	250	36	290/640	497	119	5.3
	130/80-12	69J	4	TL	3.00	2.75/3.50	250	36	325/715	513	139	5.3
	100/90-12	59J	4	TL	2.50	2.15/2.75	250	36	243/535	485	101	5.0
	110/90-12	69M	4	TL	2.50	2.15/2.75	280	41	325/715	503	109	5.6
	110/100-12	67P	4	TL	2.50	2.15/2.75	250	36	307/675	525	109	5.6
	130/60-13	60P	4	TL	3.50	3.00/3.75	280	41	250/565	486	129	5.3
	140/60-13	57L	4	TL	3.75	3.50/4.00	230	33	230/505	498	139	5.3
	130/70-13	63P	4	TL	3.50	3.00/3.75	280	41	272/600	512	129	5.3
	110/90-13	56P	4	TL	2.50	2.15/2.75	230	33	224/495	528	109	5.6
	140/60-14	64S	4	TL	3.75	3.50/4.00	280	41	280/615	524	139	5.3
	120/70-14	61S	4	TL	3.50	3.00/3.75	280	41	257/565	524	122	5.3
	140/70-14	68S	4	TL	3.75	3.50/4.00	280	41	315/695	552	139	5.3
	100/80-16	56P	4	TL	2.50	2.15/2.75	280	41	224/495	566	101	5.6
	120/80-16	60P	4	TL	2.75	2.50/3.00	230	33	250/565	598	119	6.7
	130/80-16	64P	4	TL	3.00	2.75/3.50	230	33	280/615	614	129	6.7
	120/90-16	63P	4	TL	2.75	2.50/3.00	230	33	272/600	622	119	4.6
	130/70-17	62L	4	TL	3.50	3.00/3.75	230	33	265/585	614	129	6.2
	100/80-17	52L	4	TL	2.50	2.15/2.75	230	33	200/440	592	101	4.2
D808	90/90-10	50L	4	TL	2.15	1.85/2.50	250	36	190/420	416	90	6.0
	100/90-10	56L	4	TL	2.50	2.15/2.75	250	36	224/495	434	101	6.0
D809	100/90-10	56L	4	TL	2.50	2.15/2.75	250	36	224/495	434	101	5.8
	120/90-10	66L	4	TL	2.75	2.50/3.00	250	36	300/660	470	119	4.6
	130/90-10	70L	4	TL	3.00	2.75/3.50	250	36	335/740	488	129	4.6
	120/70-12	58P	4	TL	3.50	3.00/3.75	280	41	236/520	473	122	6.0
	130/70-12	62P	4	TL	3.50	3.00/3.75	280	41	265/585	487	129	6.0
D810	4.50-10C	76L	8	TT	3.50	3.00/3.75	325	47	400/880	490	125	7.0
	4.00-12	78L	8	TT	3.00	2.75/3.50	325	47	425/935	517	105	6.0
D811	3.50-8	46J	4	TT	2.50	2.15/2.75	250	36	170/375	386	92	5.5

**D812****D813****D814****D815****D817****D818****D819****D820**

PATTERN NAME	SIZE	LI/SS	PR	TYPE	RIM (inch)		INFLATION		MAX. LOAD kg/lbs.	DIMENSION (mm)		TREAD DEPTH (mm)
					RECOM	ALTER	kPa	PSI		OD	SW	
D812	3.50-10	51J	4	TT	2.50	2.15/2.75	250	36	195/430	437	92	5.5
D813	2.75-10	38J	4	TL	1.85	1.60/2.15	250	36	132/290	399	71	4.0
	3.00-10	42J	4	TT	2.15	1.85/2.50	250	36	150/330	413	80	5.0
	3.50-10	51J	4	TL	2.50	2.15/2.75	250	36	195/430	437	92	5.8
D814	5.4-6	57B	4	TT	3.50	3.00/3.75	250	36	230/505	380	126	4.6
D815	80/80-16	45P	4	TL	1.85	1.60/2.15	280	41	165/365	534	80	4.5
	90/80-16	51P	4	TL	2.15	1.85/2.50	280	41	195/430	550	90	5.0
D817	4.00-12	65L	6	TT	2.50	2.15/2.75	250	36	290/640	517	108	6.0
		65L	6	TL	2.50	2.15/2.75	250	36	290/640	517	108	6.0
		78L	8	TT	2.50	2.15/2.75	325	47	425/935	517	108	6.0
		78L	8	TL	2.50	2.15/2.75	325	47	425/935	517	108	6.0
D818	120/70-10	48M	4	TL	3.50	3.00/3.75	230	33	180/395	422	122	5.3
D819	120/70-14	61S	4	TL	3.50	3.00/3.75	280	41	257/565	524	122	4.8
	110/80-17	62S	6	TL	2.50	2.15/2.75	280	41	265/585	608	109	6.2
	100/90-17	61S	6	TL	2.50	2.15/2.75	280	41	257/565	612	101	6.2
	120/70-17	64S	6	TL	3.50	3.00/3.75	280	41	280/615	600	122	6.2
D820	150/70-14	72S	4	TL	4.25	4.00/4.50	280	41	355/785	566	151	6.8
	120/80-17	67S	6	TL	2.75	2.50/3.00	280	41	307/675	624	119	6.2



D821

D822

D823

D824

D825

D828

D831

PATTERN NAME	SIZE	LI/SS	PR	TYPE	RIM (inch)		INFLATION		MAX. LOAD	DIMENSION (mm)		TREAD DEPTH (mm)
					RECOM	ALTER	kPa	PSI		OD	SW	
D821	100/80-10	53M	4	TL	2.50	2.15/2.75	250	36	206/455	414	101	5.6
	120/70-10	62M	4	TL	3.50	3.00/3.75	280	41	265/585	422	122	5.3
	110/70-11	45L	4	TL	3.00	2.75/3.50	230	33	165/365	433	110	5.3
D822	90/90-10	50L	4	TT	2.15	1.85/2.50	250	36	190/420	416	90	5.6
		50L	4	TL	2.15	1.85/2.50	250	36	190/420	416	90	5.6
	100/80-10	53L	4	TT	2.50	2.15/2.75	250	36	206/455	414	101	5.6
		53L	4	TL	2.50	2.15/2.75	250	36	206/455	414	101	5.6
	100/90-10	56L	4	TT	2.50	2.15/2.75	250	36	224/495	434	101	5.6
		56L	4	TL	2.50	2.15/2.75	250	36	224/495	434	101	5.6
	120/90-10	66L	4	TT	2.75	2.50/3.00	250	36	300/660	470	119	5.6
		66L	4	TL	2.75	2.50/3.00	250	36	300/660	470	119	5.6
	130/90-10	61M	4	TL	3.00	2.75/3.50	250	36	257/565	488	129	5.6
	90/90-12	54J	4	TL	2.15	1.85/2.50	250	36	212/465	467	90	5.0
D823	125-12C	62J	4	TL	3.50	3.00/3.75	250	36	265/585	565	134	6.0
		81J	8	TL	3.50	3.00/3.75	500	73	462/1020	565	134	6.0
D824	110/80-14	53P	4	TT	2.50	2.15/2.75	230	33	206/455	532	109	4.7
		59P	6	TL	2.50	2.15/2.75	280	41	243/535	532	109	4.7
D825	120/70-10	54L	6	TL	3.50	3.00/3.75	280	41	212/465	442	122	5.0
	100/80-10	58L	6	TL	2.50	2.15/2.75	280	41	236/520	414	101	5.5
	3.50-10	51J	4	TL	2.50	2.15/2.75	250	36	195/430	437	92	5.5
	110/70-11	45L	4	TL	3.00	2.75/3.50	230	33	165/365	433	110	5.0
	120/70-11	56M	6	TL	3.50	3.00/3.75	280	41	224/495	477	122	4.0
	120/70-12	58P	6	TL	3.50	3.00/3.75	280	41	236/520	473	122	5.0
	130/70-12	62P	6	TL	3.50	3.00/3.75	280	41	265/585	487	129	5.0
	150/70-14	72S	6	TL	4.25	4.00/4.50	280	41	355/785	556	151	6.5
	120/70-15	56S	4	TL	3.50	3.00/3.75	230	33	224/495	549	122	4.0
	110/70-16	52S	4	TL	3.00	2.75/3.50	230	33	200/440	560	110	6.0
	130/70-16	61S	4	TL	3.50	3.00/3.75	230	33	257/565	588	129	5.0
	140/70-16	65S	4	TL	3.75	3.50/4.00	230	33	290/640	602	139	5.5
D828	80/90-10	44J	4	TL	1.85	1.60/2.15	250	36	160/355	398	80	4.5
	3.00-10	42J	4	TT	2.15	1.85/2.50	250	36	150/330	413	80	4.5
	3.50-10	51J	4	TL	2.50	2.15/2.75	250	36	195/430	437	92	5.5
D831	3.00-10	42J	4	TL	2.15	1.85/2.50	250	36	150/330	413	80	4.5

HEAVY DUTY TIRE

**D830****D974****D980****D985**

PATTERN NAME	SIZE	LI/SS	PR	TYPE	RIM (inch)		INFLATION		MAX. LOAD	DIMENSION (mm)		TREAD DEPTH (mm)
					RECOM	ALTER	kPa	PSI		OD	SW	
D830	4.00-8	76E	6	TT	3.00	2.75/3.50	425	61	400/880	415	114	8.0
	4.50-10	85E	8	TT	3.50	3.00/3.75	500	72	515/1140	490	125	8.0
D974	3.00-16	48P	6	TT	1.85	1.60/2.15	280	41	180/395	576	80	7.0
	3.25-16	55P	6	TT	2.15	2.15/2.50	280	41	218/480	588	89	8.0
	2.50-17	43P	6	TT	1.60	1.40	280	41	155/340	568	65	6.3
	2.75-17	47P	6	TT	1.85	1.60	280	41	175/385	588	75	7.0
	3.00-17	50P	6	TT	1.85	1.60/2.15	280	41	190/420	602	80	7.0
	2.75-18	48P	6	TT	1.85	1.60	280	41	180/395	613	75	7.0
	3.00-18	52P	6	TT	1.85	1.60/2.15	280	41	200/440	627	80	7.0
D980	3.00-16	48P	6	TT	1.85	1.60/2.15	280	41	180/395	576	80	7.0
	2.50-17	43P	6	TT	1.60	1.40	280	41	155/340	568	65	6.3
	2.75-17	47P	6	TT	1.85	1.60	280	41	175/385	588	75	7.0
	3.00-17	50P	6	TT	1.85	1.60/2.15	280	41	190/420	602	80	7.0
	2.75-18	48P	6	TT	1.85	1.60	280	41	180/395	613	75	7.0
	3.00-18	52P	6	TT	1.85	1.60/2.15	280	41	200/440	627	80	7.0
D985	3.00-16	48P	6	TT	1.85	1.60/2.15	280	41	180/395	576	80	8.5
	2.50-17	43P	6	TT	1.60	1.40	280	41	155/340	568	65	7.0
	2.75-17	47P	6	TT	1.85	1.60	280	41	175/385	588	75	8.0
	3.00-17	50P	6	TT	1.85	1.60/2.15	280	41	190/420	602	80	8.5
	2.75-18	48P	6	TT	1.85	1.60	280	41	180/395	613	75	8.0
	3.00-18	52P	6	TT	1.85	1.60/2.15	280	41	200/440	627	80	8.5

INNER TUBE

INNER TUBE



VALVE



BUTYL RUBBER TUBE

RIM	SIZE	VALVE
8"	3.00-8	TR13
	3.00-8	TR87
	3.00/3.50-8	TR87
	3.50-8	TR13
	3.50-8	TR87
10"	2.75/3.00-10	TR4
	2.75/3.00-10	TR87
	3.00/3.50-10	TR4
	3.00/3.50-10	TR87
	3.50-10	TR4
	3.50-10	TR87
16"	2.25/2.50-16	TR4
	2.75/3.00-16	TR4
17"	2.00/2.25-17	TR4
	2.50-17	TR4
18"	2.50/2.75-18	TR4
	2.75/3.00-18	TR4
	3.25/3.50/4.10-18	TR4
21"	2.75/3.00-21	TR4

NATURAL RUBBER TUBE

RIM	SIZE	VALVE
8"	3.50-8	TR13
	3.50-8	TR87
10"	3.00/3.50-10	TR4
	3.00/3.50-10	TR87
	3.50-10	TR4
12"	3.50-10	TR87
	2.75/3.00-12	TR4
	2.75/3.00-12	TR87
14"	3.50/4.00-12	TR4
	3.50/4.00-12	TR13
16"	2.00-14S	TR4
	2.50-14	TR4
	2.75/3.00-14	TR4
18"	2.00/2.25-16	TR4
	2.25/2.50-16	TR4
	2.50-16	TR4
	2.75/3.00-16	TR4
	3.25/3.50-16	TR4
	110/90-16	TR4
	1.85-17, 50/90-17	TR4
20"	50/90-17	TR4
	2.00-17S	TR4
	2.00/2.25-17	TR4
	2.25/2.50-17	TR4
	2.50-17	TR4
	2.75/3.00-17	TR4
	2.25/2.50-18	TR4
22"	2.50-18	TR4
	2.75/3.00-18	TR4
	3.25/3.50/4.10-18	TR4
	100/110/120-18	TR4
	2.25/2.50-19	TR4
24"	2.75/3.00-19	TR4
	100/110/120/90-19	TR4
	2.75/3.00-21	TR4

SAFETY INFORMATION

Choose the Right Tire

When you choose new Deestone motorcycle tires, make sure they are the right for your motorcycle. Double check the size and intended usage and make sure you have made the right selection.

Tire Mounting

We recommend you to permit only specially trained persons to mount your tires. Improper mounting can damage the tires and your motorcycle, and could cause serious injury.

- Only mount front tires on the front and rear tires on the rear of your motorcycle.
- Never mount anything other than motorcycle tires on motorcycle wheels.
- Whenever possible, match front/rear tires for maximum performance and handling.
- A new tube (if required) and rim band should also be installed at this time.
- After proper tire selection, prepare the rim for mounting and clean and lubricate the tire bead.
- If you are mounting a directional tire, mount in the direction of the arrow.
- Seat the bead by inflating to half pressure. Rotate tire to make sure that it is seated properly.
- If not, remove the tire and re-mount. We do not recommend the use of rubber to help bead seating. If the tire has a tube, deflate, then re-inflate the tube after the bead has seated to eliminate wrinkles and folds. Inflate to recommended pressure and re-inspect for correct seating and alignment.
- Check pressure at regular intervals and keep tire properly inflated. DO NOT exceed recommended pressure.(found on the sidewall) Failure to follow these guidelines can result in accelerated tread wear and may cause catastrophic tire failure.

Tube Type or Tubeless

Fitting of tires to a motorcycle should be in accordance with what is written in the owner's manual.

Storage

- Store tires in a safe place at a constant temperature.
- DO NOT store tires in direct sunlight for extended periods of time.
- DO NOT expose tires to oil or gasoline as it has an adverse affect on the rubber compounds that make up a tire.

Rim Size

Clearance around tires must be maintained. Increasing tire size may increase rim width. Inspect tires closely for sufficient clearance.

Tire clearances are important.

Tire Repair

Small tread area punctures can repaired by qualified tire repair shops or motorcycle shops. The repair is solely responsible for the repair and any instructions to the repaired tire user. We do not recommend the repair of tube type motorcycle tire and also tube.

Tube type and tubeless tires with following situations can not be repaired.

- Puncture in sidewall
- Separation of any components (tread, plies, etc.)
- Size of puncture is larger than 1/4 inch
- Damage of tire cord
- Damage of bead
- Cracks

Tubes

- When fitting a new tire on rim requiring a tube, a new tube should be fitted at the same time. Old tubes become stretched and if an old tube is fitted within a new tire, it can crease and fail due to thinness of the tube rubber. Tubes should be repaired only by an expert. Inspect rim band and consult motorcycle dealer for correct rim band replacement. Check valve cores, tighten for correct seating, or remove and replace them. Protect valve core from dust, moisture to help maintain a positive air seal.
- Always check the size markings on the tube to make sure the tube size markings match the tire size.
- DO NOT fit tubes in radial motorcycle tires, not fit radial tires on rims requiring tubes, unless the tubes bear matching size and radial (R) markings.

ข้อมูลเพื่อความปลอดภัย

การเลือกยางให้เหมาะกับรถจักรยานยนต์

เมื่อคุณเลือกซื้อยางรถจักรยานยนต์ดีสโตน ควรตรวจสอบให้แน่ใจว่ายางนั้นมีขนาดพอดีกับรถของคุณ ตรวจสอบเช็คนาดของยางและวัสดุประสงค์การใช้งานอีกครั้งเพื่อให้แน่ใจว่าคุณเลือกยางได้อย่างถูกต้อง

การประกอบยาง

ควรให้ผู้เชี่ยวชาญที่ได้รับการฝึกอบรมมาโดยเฉพาะเพื่อเปลี่ยนในยาง เพราะหากใส่ยางไม่ถูกต้องอาจก่อให้เกิดความเสียหายกับยางและรถจักรยานยนต์ และอาจก่อให้เกิดอันตรายที่รุนแรงในการขับขี่ได้ โดยมีข้อแนะนำดังต่อไปนี้

- ประกอบยางหน้ากับล้อหน้าและประกอบยางหลังกับล้อหลังรถจักรยานยนต์เท่านั้น
- ไม่ควรใส่สิ่งอื่นใดนอกเหนือจากยางลงบนล้อรถจักรยานยนต์
- เพื่อการควบคุมการขับขี่ได้ดีและเพื่อให้ได้ประสิทธิภาพสูงสุดควรจับคู่ยางหน้าและยางหลังเวลาประกอบล้อรถ
- ควรเปลี่ยนยางในใหม่พร้อมกันไปด้วยและจะต้องติดตั้งยางกันกระแทกเข้าไปด้วยในเวลาเดียวกัน
- เตรียมวงล้อสำหรับประกอบ ทำความสะอาดวงล้อพร้อมกับล้อเส้นขอบล้อ
- ประกอบยางไปตามทิศทางของลูกศรที่ระบุข้างแก้มยาง
- จัดขอบล้อให้เข้าที่และเติมลมยางครึ่งหนึ่ง หมุนยางเพื่อเช็คให้แน่ใจว่ายางนั้นได้ประกอบเข้ากับวงล้อได้พอดี
- หากยางยังไม่เข้าที่ให้ถอดยางออกและประกอบเข้าไปใหม่ ปลดลมออก จากนั้นให้เติมลมเข้ายางในใหม่หลังจากที่ขอบล้อเข้าที่ดีแล้วเติมลมตามที่แนะนำและตรวจสอบอีกครั้งว่าขอบยางเข้าที่ดีและตั้งเป็นแนวตรง
- ตรวจสอบเช็คลมยางเพื่อให้ยางนั้นมีลมพอดี ไม่ควรเติมลมยางมากกว่าหรือน้อยกว่าที่แนะนำ (ดูจากข้อมูลที่ระบุไว้ที่แก้มยาง)

หากไม่ทำตามคำแนะนำที่ระบุไว้ อาจทำให้ยางมีอัตราการสึกเร็วกว่าปกติและอาจก่อให้เกิดความเสียหายกับยาง

ยางที่ใช้ยางในและยางที่ไม่มียางใน

การประกอบยางเข้ากับรถจักรยานยนต์ควรจะให้สอดคล้องกับคู่มือการใช้งานของรถ

การเก็บรักษายาง

- ควรเก็บยางไว้ในที่ๆ ปลอดภัยและมีอุณหภูมิคงที่
- ไม่ควรนำยางมาวางตากแดดเพราะแสงแดดและความร้อนจะทำให้ยางเสื่อมคุณภาพเร็วขึ้น
- ไม่ควรให้ยางเปื้อนน้ำมันหรือแก๊สซึ่งมีผลต่อเนื้อยาง ถ้ายางเปื้อนควรเช็ดรอยเปื้อนต่างๆ ออกทั้งหมดทันที

ขนาดของล้อ

ดูแลความสะอาดของยางเสมอ ยางที่ขนาดใหญ่ขึ้นอาจจะต้องประกอบกับล้อที่ใหญ่ขึ้นเช่นกัน หากวงล้อแคบจะทำให้ยางเสียรูปทรงและหน้ายางสึกมากในบริเวณแคบๆ

การซ่อมยาง

รอยร้าวเพียงเล็กน้อยสามารถซ่อมได้โดยร้านซ่อมหรือร้านขายรถจักรยานยนต์ที่มีศูนย์บริการ ช่างซ่อมมีหน้าที่ซ่อมแซมและให้คำแนะนำกับผู้ใชยางยางนอกที่ใช้ยางในและยางที่ไม่มียางในไม่สามารถนำไปซ่อมได้หากเกิดกรณีต่างๆ ดังนี้

- มีรูรั่วที่แก้มยาง
- ส่วนประกอบต่างๆ แยกออกจากกัน (เช่น หน้ายาง ชั้นผ้าใบ เป็นต้น)
- ขนาดของรูรั่วใหญ่เกินกว่า 1/4 นิ้ว
- ผ้าใบเสียหาย
- ขอบล้อเสียหาย
- เกิดรอยแตกตรงแก้มยางและดอกยาง

ยางใน

- เมื่อมีการประกอบยางใหม่เข้ากับวงล้อหากยางนั้นต้องใชยางในก็ควรต้องเปลี่ยนใหม่เช่นเดียวกัน ยางในเก่าจะเริ่มยึดและ หากประกอบยางในเก่าเข้ากับยางนอกใหม่ยางในอาจมีรอยพับหลังจากประกอบเสร็จ ยางในควรได้รับการซ่อมแซมโดยผู้ที่มีความชำนาญเท่านั้น ตรวจสอบเช็คนาดยางกันกระแทกและปรึกษาตัวแทนจำหน่ายเพื่อเปลี่ยนยางกันกระแทกได้ถูกต้อง
- ตรวจสอบเช็ควาล์วยางใน เช็คทำความสะอาดถ้าเปื้อนฝุ่นหรือมีความชื้น วาล์วยางในควรประกอบกับวงล้ออย่างระมัดระวัง
- ตรวจสอบเช็คนาดยางในเสมอเพื่อให้แน่ใจว่าขนาดตรงกับขนาดของยางนอก ห้ามประกอบยางเรเดียลเข้ากับวงล้อที่ใช้กับยางใน



DEESTONE CORPORATION LIMITED

84 Soi Phet Kasem 122 , Moo 7, Phet Kasem Road , Om Noi , Krathum Baen,
Samut Sakhon , 74130 , THAILAND

Tel : (+662) 420-0038 , 023-4756

Fax : (+662) 420-0572 , 023-4724

E-mail : deestone@deestone.com



www.facebook.com/Deestonetyre



www.deestone.com



Deestonetyre

